



Holder / No. 570

Panel Mount, for TR5®/TE5® Fuses



Panel alternatives



with cap 575 IP40
(only on front side)



Specifications

Packaging

000 bulk (100 pcs.)

Order Number

Holder No. 570 0000 000

Mounting

12.7mm diameter D-hole or double D-hole
Admissible torque on plastic hex nut is 1.2Nm

Terminals

Solderable or 2.8mm quick connect-fits 0.5mm tab

Materials

Holder: Black Thermoplastic, UL 94 V-0
Polyamide PA 6.6
Metal parts: Copper alloy
Solderable tinned

Electrical Data (23°C/without Cap)

Rated Voltage: 250V
Max. Current/Power: 6.3A/2.5W

Minimum Cross Section

Conductor - 2.5mm²

Unit Weight


2.2g

Order Information

Qty.	Order-Number	Series	Packaging
		570	0000 000

Specifications are subject to change without notice

Cap / No. 575



Packaging

000 bulk (100 pcs.)

Order Number

Cap No. 575 0000 000

Plastic Cap

Use with No. 570 or No. 571

Materials

Cap: Transparent Thermoplastic
Polycarbonat PC, UL94 V-0

Unit Weight

0.94g

Order Information

Qty.	Order-Number	Series	Packaging
		575	0000 000



Specifications are subject to change without notice

Holder / No. 571

PC Mount, for TR5®/TE5® Fuses



Holes in PCB



Packaging

000 bulk (100 pcs.)

Order Number

Holder No. 571 0000 000

Mounting

PC Board, 7.62mm hole spacing

Materials

Holder: Black Thermoplastic, UL94 V-0
Polyamide PA 6.6
Metal parts: Copper alloy
Solderable, tinned

Electrical Data (23°C/without Cap)

Rated Voltage: 250V
Max. Current/Power: 6.3A/2.5W

Minimum Cross Section

Conducting path - 0.2mm²

Unit Weight

1.6g

Order Information

Qty.	Order-Number	Series	Packaging
		571	0000 000

Specifications are subject to change without notice