



Coax Adapter Kit/BNC to BNC/F Series C

[home](#) | [faq](#) | [corporate story](#) | [contact us](#) | [messageboard](#)

Technicians and engineers turn to TPI for their connecting needs

NEW PRODUCTS!

707 Carbon Monoxide Analyzer

708 Combustion Efficiency Analyzer

712 Flue Gas Analyzer

A740 Infrared Printer

Tuffman Manometer

460 Handheld Oscilloscope

440 True RMS Digital Multimeter

Digital Multimeters

Digital Clamp-On Meters

DMM and Clamp-On Accessories

DMM and Scope Accessories Guide

Infrared Non-Contact Thermometers

Temperature Instruments

Pocket Digital Thermometers

Thermocouple Temperature Probes

Digital Manometers

Refrigerant Leak Detectors

CO Analyzer and Gas Detection Instruments

Differential Probes

Oscilloscope Probes

Surface Mount Test Clips

Coax Adapter Kit BNC to BNC F Series Cables

Coax Adapter Connector Kit TPI-3000A

With this versatile kit the technician can create connections on the spot in seconds. All 8 types of male and female adapters are included. Just screw on any combination of 24 connectors to any of six universal interfaces. No soldering or crimping need. Connectors are reusable and can be used over and over in different combinations to fit and assist customizing the installation. All contacts are gold plated. Connector bodies are silver plated machined brass with Teflon insulation. The zippered, soft case protects and organizes the collection. **TPI-3000A**



BNC to BNC Coax Cable



- UL listed cable
- Boot is molded to cable and connector for added strength
- Gold center pins
- Machined brass connectors
- 95% shielding
- 80°F temp rating
- Lengths up to 100 ft

RG58/U BNC Male-to-Male Instrumentation and Data 50 Ohm

Part	Length
58-012-1M	12 inches
58-024-1M	24 inches
58-036-1M	36 inches
58-046-1M	48 inches
58-060-1M	60 inches
58-072-1M	72 inches
58-120-1M	10 feet
58-180-1M	15 feet
58-300-1M	25 feet
58-600-1M	50 feet
58-900-1M	75 feet
58-1200-1M	100 feet

RG59/U Male-to-Male Video and General 75 Ohm

Part	Length
59-012-1M	12 inches
59-024-1M	24 inches
59-036-1M	36 inches
59-046-1M	48 inches
59-060-1M	60 inches
59-072-1M	72 inches
59-120-1M	10 feet

RG62/U BNC Male-to-Male Computer and Laboratory 93 Ohm

Part	Length
62-024-1M	24 inches
62-036-1M	36 inches
62-048-1M	48 inches
62-060-1M	60 inches

BNC to BNC Cable Assemblies 50 Ohm

Part	Length
------	--------

59-180-1M	15 feet	58-024-1A	24 inches
59-300-1M	25 feet	58-036-1A	36 inches
59-600-1M	50 feet	58-048-1A	48 inches
59-1200-1M	100 feet	58-060-1A	60 inches

Screw-on F-Cables



- UL listed cable
- RG6
- Molded Ends
- Lengths up to 100 ft
- Black or white cable

F-Series Cables RG-6 Video and General

Black

Part	Length
F6-3B	3 feet
F6-6B	6 feet
F6-10B	10 feet
F6-12B	12 feet
F6-15B	15 feet
F6-25B	25 feet
F6-50B	50 feet
F6-75B	75 feet
F6-100B	100 feet

White

Part	Length
F6-3W	3 feet
F6-6W	6 feet
F6-10W	10 feet
F6-12W	12 feet
F6-15W	15 feet
F6-25W	25 feet
F6-50W	50 feet
F6-75W	75 feet
F6-100W	100 feet