

7110A Non-Paired - 600V C-TC+ Control Cables for Extreme Flexing

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

18 AWG stranded (114x38) bare copper conductors, PVC insulation, unshielded. oil- and abrasion-resistant PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	3
Total Number of Conductors	3
AWG	18
Stranding	114x38
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.020 in.
Insulation Resistance	6.1 Megaohms/1000 ft. minimum.

Insulation Color Code Chart :

Number	Color	Number	Color
1	Red #1	3	Green/Yellow
2	Red #2		

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.035 in.

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.300 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +90°C
Other Temperature Range	Flexing: -5°C To +90°C
UL Temperature Rating	90°C (UL AWM Style 2587)
Bulk Cable Weight	46 lbs/1000 ft.
Max. Recommended Pulling Tension	69 lbs.

7110A Non-Paired - 600V C-TC+ Control Cables for Extreme Flexing

Min. Bend Radius (Continuous Flexing)	2.8 in.
Flex Cycle Rating	9 Million Flexes

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

AWM Specification	UL Style 2587 (600 V 90°C)
CSA Specification	AWM I A/B II A/B
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005

FLAME TEST:

UL Flame Test	UL1685 UL Loading, VW-1
CSA Flame Test	FT1

SUITABILITY:

Oil Resistance	Yes
----------------	-----

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Conductor DC Resistance @ 20 Deg. C	5.7 Ohms/1000 ft
Max. Operating Voltage - UL	600 V RMS (UL AWM Style 2587)

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
7110A 0031000	3C 18 114/38 BC PVC PVC	1000	50	ORANGE	C Z
7110A 003500	3C 18 114/38 BC PVC PVC	500	26	ORANGE	C Z

C = CRATE REEL PUT-UP.

Z = FINAL PUT-UP LENGTH MAY VARY (+ OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

Revision Number: 1 Revision Date: 10-10-2005

7110A Non-Paired - 600V C-TC+ Control Cables for Extreme Flexing

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.