




- 3-Terminal Regulators
- Output Current up to 100 mA
- No External Components
- Internal Thermal-Overload Protection
- Internal Short-Circuit Current Limiting
- Direct Replacements for Fairchild μ A78L0 Series



description

This series of fixed-voltage integrated-circuit voltage regulators is designed for a wide range of applications. These applications include on-card regulation for elimination of noise and distribution problems associated with single-point regulation. In addition, they can be used with power-pass elements to make high-current voltage regulators. One of these regulators can deliver up to 100 mA of output current. The internal limiting and thermal-shutdown features of these regulators make them essentially immune to overload. When used as a replacement for a zener diode-resistor combination, an effective improvement in output impedance can be obtained, together with lower bias current.



electrical characteristics at specified virtual junction temperature, $V_I = 1$ V, $I = 40$ mA (unless otherwise noted)

PARAMETER	TEST CONDITIONS	T ‡				UNIT
			MIN	TYP	MAX	
Output voltage		25°C				V
	V_O	Full range				
	$I_O = 1$ mA to 70 mA	Full range				
Input voltage regulation	$V_I =$	°				
	$V_I =$					
Ripple rejection	$V_I =$	25°C				dB
Output voltage regulation	$I_O = 1$ mA to 100 mA	°				
	$I_O = 1$ mA to 40 mA					
Output noise voltage	$f = 10$ Hz to 100 kHz	25°C				μ V
Dropout voltage		25°C		1.7		V
		25°C			6	
		125°C			5.5	
Bias current change	$V_I =$	range			1.5	
	$I_O = 1$ mA to 40 mA				0.1	

‡ Pulse testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33- μ F capacitor across the input and a 0.1- μ F capacitor across the output. Full range for the 78L05 is $T_J = 0^\circ\text{C}$ to 70°C



		UNIT
Input voltage, V_I		V
Virtual junction temperature range, T_J	150	°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	260	°C
Storage temperature range, T_{stg}	–65 to 150	°C

	MIN	MAX	UNIT
Input voltage, V_I			
Output current, I_O		100	mA
Operating virtual junction temperature, T_J	0		°C
