


- 3-Terminal Regulators
- Output Current up to 100 mA
- No External Components
- Internal Thermal-Overload Protection
- Internal Short-Circuit Current Limiting
- Direct Replacements for Fairchild μ A78L Series



description

This series of fixed-voltage integrated-circuit voltage regulators is designed for a wide range of applications. These applications include on-card regulation for elimination of noise and distribution problems associated with single-point regulation. In addition, they can be used with power-pass elements to make high-current voltage regulators. One of these regulators can deliver up to 100 mA of output current. The internal limiting and thermal-shutdown features of these regulators make them essentially immune to overload. When used as a replacement for a zener diode-resistor combination, an effective improvement in output impedance can be obtained, together with lower bias current.



electrical characteristics at specified virtual junction temperature, $V_I =$ otherwise noted)

PARAMETER	TEST CONDITIONS	T $\pm$				UNIT
			MIN	TYP	MAX	
Output voltage		25°C				V
		Full range				
	$I_O = 1 \text{ mA to } 70 \text{ mA}$	Full range				
Input voltage regulation	$V_I =$	°				
	$V_I =$					
Ripple rejection	$V_I =$ $f = 120 \text{ Hz}$	25°C				dB
Output voltage regulation	$I_O = 1 \text{ mA to } 100 \text{ mA}$	°				
	$I_O = 1 \text{ mA to } 40 \text{ mA}$					
Output noise voltage	$f = 10 \text{ Hz to } 100 \text{ kHz}$	25°C				μV
Dropout voltage		25°C				V
		25°C			6	
		125°C			5.5	
Bias current change	$V_I =$	range			1.5	
	$I_O = 1 \text{ mA to } 40 \text{ mA}$				0.1	

† Pulse testing techniques maintain T_J as close to T_A as possible. Thermal effects must be taken into account separately. All characteristics are measured with a 0.33- μF capacitor across the input and a 0.1- μF capacitor across the output. Full range for the 78L05 is $T_J = 0^\circ\text{C to } 70^\circ\text{C}$

		UNIT
Input voltage, V_I		V
Virtual junction temperature range, T_J	150	°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds	260	°C
Storage temperature range, T_{Stg}	–65 to 150	°C

	MIN	MAX	UNIT
Input voltage, V_I			
Output current, I_O		100	mA
Operating virtual junction temperature, T_J	0		°C
