

83242 Coax - 50 Ohm Coax



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

18 AWG solid .037" silver-coated copper-covered steel conductor, plenum, TFE Teflon® insulation, double silver-coated copper braid shield (96% coverage), FEP jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	142B/U
AWG	18
Stranding	Solid
Conductor Diameter	.037 in.
Conductor Material	SCCCS - Silver-coated Copper-covered Steel

INSULATION:

Insulation Material Trade Name	Teflon®
Insulation Material	TFE - Tetrafluoroethylene
Insulation Diameter	.116 in.

OUTER SHIELD:

Outer Shield Type	Braid/Braid
-------------------	-------------

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1		Braid	Silver-coated Copper	96
1		Braid	Silver-coated Copper	94

Outer Shield %Coverage	96 %
------------------------	------

OUTER JACKET:

Outer Jacket Material	FEP - Fluorinated Ethylene Propylene
-----------------------	--------------------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.195 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-70°C To +200°C
UL Temperature Rating	200°C

83242 Coax - 50 Ohm Coax

Bulk Cable Weight	43 lbs/1000 ft.
Max. Recommended Pulling Tension	146 lbs.
Min. Bend Radius (Install)	2 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMP
CEC/C(UL) Specification	CMP
EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
Military Specification	MIL-C-17G, M17/158-00001

FLAME TEST:

UL Flame Test	VW-1, NFPA 262
C(UL) Flame Test	FT6

OTHER:

Other Information (Trademarks)	Teflon® is a DuPont trademark
--------------------------------	-------------------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	Y
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	50 Ohms
Nom. Inductance	.067 µH/ft
Nom. Capacitance Conductor to Shield	29.0 pF/ft
Nominal Velocity of Propagation	70% %
Nominal Delay	1.48 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	19.3 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20°C	2.3 Ohms/1000 ft
Nom. Attenuation :	

83242 Coax - 50 Ohm Coax

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	10			1.1
	50			2.6
	100			3.8
	200			5.4
	400			7.9
	700			10.7
	900			12.3
	1000			13.1
	2000			19.3
	3000			24.2
	5000			32.6
	8000			43.2

Max. Operating Voltage - UL 150 V RMS

Max. Operating Voltage - Other 1400 V RMS (Military)

NOTES:

Notes Non-SWR swept version of RG-142. Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
83242 001100	#18H COAX RG-142B/U	100	5.3	BROWN	C E
83242 0011000	#18H COAX RG-142B/U	1000	46	BROWN	C E
83242 001500	#18H COAX RG-142B/U	500	22.5	BROWN	C E

C = CRATE REEL PUT-UP.

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

Revision Number: 3 Revision Date: 11-29-2005

83242 Coax - 50 Ohm Coax

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.