

8460 Non-Paired - High-Conductivity Copper Speaker Cable Open Twisted Const

		<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--	---

Description:

18 AWG stranded (7x26) ETP high-conductivity tinned copper conductors, PVC insulation, cabled, (color code: black, natural).

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	2
Total Number of Conductors	2
AWG	18
Stranding	7x26
Conductor Material	High Conductivity TC - Tinned Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.020 in.

Insulation Color Code Chart :

Number	Color	Number	Color
1	Black	2	White

OVERALL CABLING:

Overall Cabling Lay Length	2 in.
Overall Cabling Twists/ft.	6

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	Unjacketed
-----------------------	------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.180 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-30°C To +80°C
UL Temperature Rating	80°C (UL AWM Style 1007)
Bulk Cable Weight	17 lbs/1000 ft.
Max. Recommended Pulling Tension	50 lbs.

8460 Non-Paired - High-Conductivity Copper Speaker Cable Open Twisted Const

Min. Bend Radius (Install)	1.8 in.
----------------------------	---------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

AWM Specification	UL Style 1007 (300 V 80°C)
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

FLAME TEST:

UL Flame Test	VW-1
---------------	------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Inductance	.19 μ H/ft
Nom. Conductor DC Resistance @ 20 Deg. C	5.9 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS (UL AWM Style 1007)
Max. Recommended Current	5.2 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8460 0631000	TW PR BLK & NAT	1000	18	BLACK & WHITE	C
8460 063U1000	TW PR BLK & NAT	U1000	18	BLACK & WHITE	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 08-17-2005

8460 Non-Paired - High-Conductivity Copper Speaker Cable Open Twisted Const

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.