



Revision			
Rev.	Description	Date	Approved

1. PHYSICAL DIMENSIONS:



2. SCHEMATIC:



L: 2.0mH
C1: 0.22uF
C2: 2200pF
R: 1.0MΩ

1. ELECTRICAL CHARACTERISTICS:

- 1-1. VOLTAGE RATING 115/250VAC
- 1-2. CURRENT RATING
A. AT 115VAC 3 A RMS Max.
B. AT 250VAC 3 A RMS Max.
- 1-3. OPERATING FREQUENCY..... 50/60 Hz
- 1-4. LEAKAGE CURRENT: EACH LINE TO GROUND
A. @115VAC 60Hz 0.20 mA Max.
B. @250VAC 50Hz 0.40 mA Max.
- 1-5. HIPOT RATING (FOR ONE MINUTE)
A. LINE TO GROUND 2250VDC
B. LINE TO LINE 1450VDC
- 1-6. TEMPERATURE RANGE: -25 TO +85 DEGREE C
- 1-7. MINIMUM INSERTION LOSS IN dB: (AT 50 OHM SYSTEM)

FREQ. MHz	.01	.05	.10	.15	.50	1.0	5.0	10	30
COM. MODE dB	2	10	12	15	30	35	35	40	25
DIF. MODE dB	/	2	5	8	15	20	30	35	35

1-8. SAFETY    

Dim range (mm)	Tolerance +/- (mm)	Qualtek Electronics Corp. PPC DIVISION		
		Part Number: 880-03/002		
0-1	0.15	Description: EMI FILTER		
1-6	0.20			
6-18	0.30			
18-50	0.50			
50-120	0.70	Drawn/Date B.ZHANG 09-12-01	Checked/Date BAC 09-12-01	Approved/Date JJH/09-12-01
120-250	0.90			
250-500	1.20			