

DWG. NO.
SD-88732-9*00

F

D

V


C

B

DO NOT SCALE DRAWING

EC NO. DRWN: CHK'g APPR:	EC NO. DRWN: CHK'g APPR:	EC NO. DRWN: CHK'g APPR:	EC NO. DRWN: CHK'g APPR:	RELEASED EC NO. JD2000-0857 DRWN: YUKOJIMA '00/02/17 CHK'g: M.SASAO '00/02/17 APPR: H.IKESUGI '00/02/17	DESCRIPTION	MATERIAL 材料	GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差	SCALE 2-1	DESIGN UNITS ☒ mm ☐ INCH	 THIRD ANGLE PROJECTION	☐ mm INCH ☐ INCH mm ☒ mm ONLY	REVISE ON CAD ONLY		
						SEE SHEET 2	10 UNDER 未満	±0.2	TITLE: USB A-B I/O CABLE					
						SEE SHEET 2	10 OVER 30 UNDER 以上 未満	±0.25						
						SEE CHART	30 OVER 以上	±0.3	MOLEX INCORPORATED					
						SEE CHART	ANGLE 角度	±3°						
						INS. RANGE 被覆外径	SEE CHART	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.						SIZE B

BRAID/DRAIN	AWG#20	AWG#28	AWG#28	AWG#20	5.0	5010	88732-9400	4
	AWG#22	AWG#28	AWG#28	AWG#22	5.0	3340	88732-9300	
	AWG#24	AWG#28	AWG#28	AWG#24	4.7	2090	88732-9200	
	AWG#26	AWG#28	AWG#28	AWG#26	4.2	1320	88732-9100	
	AWG#28	AWG#28	AWG#28	AWG#28	4.2	820	88732-9000	
DRAIN WIRE	BLACK	GREEN	WHITE	RED	ケーブル外径 FINISH DIAMETER	A	製品番号 MATERIAL NO.	極数 CIRCUITS
ワイヤーサイズ WIRE SIZE				DIMENSIONS:			SHT	REV



887329-00.S01.DGN

DWG. NO.
SD-88732-9*00

F

D

▽

C

B

DO NOT SCALE DRAWING

8

7

6

5

4

3

2

1

F

E

D


C

B

887329*00.S02.DGN

注記)
NOTES.

1. ケーブル構造
CABLE CONSTITUTION



WIRE COLOR (SIGNAL NAME)	接点 CONTACT NUMBER	
	USB-A	USB-B
RED (V)	#1	#1
WHITE (-DATA)	#2	#2
GREEN (+DATA)	#3	#3
BLACK (GND)	#4	#4
DRAIN WIRE	SHEEL	SHEEL

2. 部品構成
PART CONSTRUCTION

	部品名 PARTS NAME	材質 MATERIALS	処理 FINISH
①	TERMINAL	銅合金 COPPER ALLOY	接点部 : 金メッキ + パラジウムニッケル CONTACT AREA : GOLD + PALLADIUM-NICKEL
②	HOUSING	GLASS FILLED HEAT RESISTANT PLASTIC + GOLD FLASH COLOR : WHITE	—— # ——
③	USB-A FRONT SHELL	鋼 STEEL	下地 : 銅めっき、光沢 半田めっき UNDER PLATING : COPPER, LIGHT TIN PLATING
④	USB-A REAR SHELL	鋼 STEEL	下地 : 銅めっき、光沢 半田めっき UNDER PLATING : COPPER, LIGHT TIN PLATING
⑤	USB-B FRONT SHELL	鋼 STEEL	下地 : 銅めっき、光沢 半田めっき UNDER PLATING : COPPER, LIGHT TIN PLATING
⑥	USB-B REAR SHELL	鋼 STEEL	下地 : 銅めっき、光沢 半田めっき UNDER PLATING : COPPER, LIGHT TIN PLATING
⑦	CRIMP HOUSING	GLASS FILLED HEAT RESISTANT PLASTIC + GOLD FLASH COLOR : WHITE	—— # ——
⑧	OVER MOLD HOUSING	POLYVINYL CHLORIDE COLOR : FROST WHITE	—— # ——

DIMENSIONS:		SHT	REV
☐ mm INCH	☐ INCH mm	☒ mm ONLY	REVISE ON CAD ONLY

EC NO. DRWN: CHK: APPR:			EC NO. DRWN: CHK: APPR:			EC NO. DRWN: CHK: APPR:			EC NO. DRWN: CHK: APPR:			RELEASED EC NO. JD2000-0857 DRWN: YUKOJIMA '00/02/17 CHK: M.SASAO '00/02/17 APPR: H.IKESUGI '00/02/17	DESCRIPTION	MATERIAL 材料 部品構成表参照 SEE PART CONSTRUCTION		GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差		SCALE 2-1	DESIGN UNITS ☑mm □INCH	 THIRD ANGLE PROJECTION	☐ mm INCH	☐ INCH mm	☒ mm ONLY	REVISE ON CAD ONLY			
														FINISH 仕上り 部品構成表参照 SEE PART CONSTRUCTION		10 UNDER 未満	±0.2	DRAWN BY & DATE Yu.Kojima '00/02/17			TITLE: USB A-B I/O CABLE						
																10 OVER 30 UNDER 以上 未満	±0.25	CHECKED BY & DATE H. Sasao '00/02/17									
																30 OVER 以上	±0.3	APPROVED BY & DATE H. Sasao '00/02/17			MOLEX INCORPORATED						
												WIRE RANGE 適用電線範囲		— # —	ANGLE 角度	±3°	CAD FILENAME 887329*00.S02		MATERIAL NO. SEE CHART	DRAWING NO. SD-88732-9*00					SHEET NO. 2 OF 2		
												REV	INS. RANGE 被覆外径	— # —			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.										SIZE B