

Arrester Blocks


E Series


Construction

- Passivated collar
- Termination: flame-sprayed
- Pressure contacts

Features

- Suitable for distribution applications (light and normal duty)
- Gapless arrester construction
- Based on IEC 60099-4 and ANSI/IEEE C62.11
- Stackable for higher voltage ratings
- Arrester blocks for stationary applications or other voltage classes and diameters (up to 100 mm) are available upon request.





Arrester Blocks

E Series

General technical data

Types	SIOV-	E32VR302	E32VR602	E42VR302	E42VR602	
Ordering codes		B72232 E0302R001	B72232 E0602R001	B72242 E0302R001	B72242 E0602R001	
Rated voltage	V_R	3	6	3	6	kV
Nominal discharge current	I_n	5	5	10	10	kA
Residual voltage at I_n	V_{res}	$\leq 9,5$	≤ 19	≤ 10	≤ 20	kV
Continuous operating voltage	V_c	2,45	4,9	2,45	4,9	kV
Power dissipation at V_c	P_c	$\leq 0,20$	$\leq 0,39$	$\leq 0,35$	$\leq 0,65$	W
Reference current	I_{ref}	1	1	2	2	mA
Reference voltage	V_{ref}	≥ 3	≥ 6	≥ 3	≥ 6	kV
Long-duration current impulse		18×150 ; 2	18×150 ; 2	18×250 ; 2	18×250 ; 2	A; ms
High-current pulse (with secondary insulation)		2×65 ; 4/10	2×65 ; 4/10	2×100 ; 4/10	2×100 ; 4/10	kA; μs
Accelerated ageing test 1000 h, 115 °C, N ₂ , V_c		permanent decrease of power dissipation				—
Operating temperature		- 25 ... + 60	- 25 ... + 60	- 25 ... + 60	- 25 ... + 60	°C
Storage temperature		- 25 ... + 80	- 25 ... + 80	- 25 ... + 80	- 25 ... + 80	°C
Metallization		Al electrodes				—
Collar		passivated				—
Diameter		34 ± 1	34 ± 1	43 ± 1	43 ± 1	mm
Thickness		$22 \pm 0,6$	$44 \pm 0,6$	$22 \pm 0,6$	$44 \pm 0,6$	mm
Marking		type, lot number, V_{res} , P_c , V_{res} class (0,1 kV steps)				—
Weight approx.		110	220	180	360	g

Device ratings and specifications at 25 °C unless otherwise specified.

Diese Broschüre ersetzt die vorige Ausgabe.

Fragen über Technik, Preise und Liefermöglichkeiten richten Sie bitte an den Ihnen nächstgelegenen oder an unsere Vertriebsgesellschaften im Ausland. Bauelemente können aufgrund technischer Erfordernisse nicht auf Lager gehalten werden. Auskünfte darüber bitten wir unter Angabe des betreffenden Typs ebenfalls über die zuständige Vertriebsgesellschaft zu erhalten.

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

☎ ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained herein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the EPCOS Group, which are recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise stated.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the representatives of the EPCOS Group in your country.

Due to technical requirements components may contain dangerous substances. For information on the handling of these components please contact one of our Sales Offices.



中发网 WWW.ZFA.CN

全球最大的PDF中文下载站



中发网
www.zfa.cn

PDF 资料下载尽在中发网