

9182 Twinax - Twinaxial Cable

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

22 AWG stranded (19x34) tinned copper conductors, Datalene® insulation, Duofoil® (100% Coverage) plus a stranded tinned copper drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	22
Stranding	19x34
Conductor Diameter	.031 in.
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material Trade Name	Datalene®
Insulation Material	FHDPE - Foam High Density Polyethylene

PAIR:

Pair Lay Length & Direction :

Lay Length (in.)	Direction	Twists/ft (twist/ft)
3.0		4

Pair Diameter .275 in.

Pair Color Code Chart :

Number	Color
1	Black & Yellow

OUTER SHIELD:

Outer Shield Trade Name	Duofoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape-Aluminum Foil
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	22
Outer Shield Drain Wire Stranding	19x34
Outer Shield Drain Wire Diameter	.031 in.

9182 Twinax - Twinaxial Cable

Outer Shield Drain Wire Conductor Material	TC - Tinned Copper
--	--------------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.345 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +60°C
Bulk Cable Weight	41 lbs/1000 ft.
Max. Recommended Pulling Tension	28 lbs.
Min. Bend Radius (Install)	3.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMX, CL2X
CEC/C(UL) Specification	CMX
AWM Specification	UL Style 2668 (30 V 60°C)
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

FLAME TEST:

UL Flame Test	UL1685 UL Loading, VW-1
---------------	-------------------------

SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes
Suitability - Aerial	Yes - when supported by a messenger wire

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	89182

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	150 Ohms
Nom. Inductance	0.293 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	8.8 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	16.5 pF/ft
Nominal Velocity of Propagation	78 %
Nominal Delay	1.3 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	14.0 Ohms/1000 ft
Nominal Outer Shield DC Resistance	6.3 Ohms/1000 ft

9182 Twinax - Twinaxial Cable

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			0.4
	10			1.2
	50			2.7
	100			4.3
	200			6.2
	400			8.8

Max. Operating Voltage - UL 300 V RMS (CMX), 30 V RMS (UL AWM Style 2668), 150 V RMS (CL2X)

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9182 0101000	2 #22 FHDPE SHLD PVC	1000	44	BLACK	C
9182 010500	2 #22 FHDPE SHLD PVC	500	23	BLACK	C
9182 010U500	2 #22 FHDPE SHLD PVC	U500	21.5	BLACK	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 12-01-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.