

9274 Coax - 75 Ohm Coax

		<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--	---

Description:

20 AWG solid .032" bare copper-covered steel conductor, foam polyethylene insulation, bare copper braid shield (95% coverage), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	59/U
AWG	20
Stranding	Solid
Conductor Diameter	.032 in.
Conductor Material	BCCS - Bare Copper Covered Steel

INSULATION:

Insulation Material	FPE - Foam Polyethylene
Insulation Diameter	.143 in.

OUTER SHIELD:

Outer Shield Type	Braid
Outer Shield Material	BC - Bare Copper
Outer Shield % Coverage	95 %

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.240 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +80°C
UL Temperature Rating	80°C
Bulk Cable Weight	30 lbs/1000 ft.
Max. Recommended Pulling Tension	86 lbs.
Min. Bend Radius (Install)	2.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

9274 Coax - 75 Ohm Coax

APPLICABLE STANDARDS:

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

FLAME TEST:

UL Flame Test	UL1685 UL Loading
---------------	-------------------

SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 Ohms
Nom. Inductance	.097 μ H/ft
Nom. Capacitance Conductor to Shield	16.3 pF/ft
Nominal Velocity of Propagation	82 %
Nominal Delay	1.24 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	44.5 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20°C	3.5 Ohms/1000 ft

Minimum Structural Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Structural Return Loss (dB)
		5	450	23

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			.6
	10			1.0
	50			2.1
	100			3.0
	200			4.5
	400			6.6
	700			8.9
	900			10.1
	1000			10.9

Max. Operating Voltage - UL	300 V RMS
-----------------------------	-----------

NOTES:

9274 Coax - 75 Ohm Coax

Notes 100% sweep tested. 5 MHz to 450 MHz.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9274 0101000	RG-59/U TYPE COAX	1000	35	BLACK	C
9274 010500	RG-59/U TYPE COAX	500	15.5	BLACK	

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 08-18-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.