

## 9908 Hook-up/Lead - UL AWM Styles 1028 and 1015

|                                                                                                                                                                      |                                                                                                           |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|
|   | <p>For more information please<br/>call<br/><b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p> |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|

### Description:

Tinned copper conductor, PVC insulation.

### PHYSICAL CHARACTERISTICS:

#### CONDUCTOR:

|                            |                    |
|----------------------------|--------------------|
| Number of Conductors       | 1                  |
| Total Number of Conductors | 1                  |
| AWG                        | 8                  |
| Stranding                  | 84x27              |
| Conductor Material         | TC - Tinned Copper |

#### INSULATION:

|                      |                          |
|----------------------|--------------------------|
| Insulation Material  | PVC - Polyvinyl Chloride |
| Insulation Thickness | .045 in.                 |

#### OVERALL:

|                          |          |
|--------------------------|----------|
| Overall Nominal Diameter | .250 in. |
|--------------------------|----------|

### APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

#### APPLICABLE STANDARDS:

|                                       |               |
|---------------------------------------|---------------|
| UL AWM Style                          | 1015 and 1028 |
| UL Rating                             | 600 V, 105°C  |
| CSA Type                              | TEW           |
| CSA Rating                            | 600 V, 105°C  |
| EU CE Mark (Y/N)                      | Yes           |
| EU RoHS Compliant (Y/N)               | Yes           |
| EU RoHS Compliance Date (mm/dd/yyyy): | 07/01/2005    |

#### FLAME TEST:

|               |      |
|---------------|------|
| UL Flame Test | VW-1 |
|---------------|------|

#### PLENUM/NON-PLENUM:

|              |   |
|--------------|---|
| Plenum (Y/N) | N |
|--------------|---|

### PUT-UPS AND COLORS:

## 9908 Hook-up/Lead - UL AWM Styles 1028 and 1015

| Item        | Description    | Put-Up (ft.) | Ship Weight (lbs.) | Jacket Color | Notes |
|-------------|----------------|--------------|--------------------|--------------|-------|
| 9908 002100 | #8 STR PVC RED | 100          | 8                  | RED          |       |
| 9908 002250 | #8 STR PVC RED | 250          | 19                 | RED          |       |
| 9908 004100 | #8 STR PVC YEL | 100          | 8                  | YELLOW       |       |
| 9908 009100 | #8 STR PVC WHT | 100          | 8                  | WHITE        |       |
| 9908 009250 | #8 STR PVC WHT | 250          | 19                 | WHITE        |       |
| 9908 010100 | #8 STR PVC BLK | 100          | 8                  | BLACK        |       |
| 9908 010250 | #8 STR PVC BLK | 250          | 19                 | BLACK        |       |

Revision Number: 1      Revision Date: 04-26-2005

© Copyright 2006 Belden, Inc  
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.