

9924 Hook-up/Lead - UL AWM Style 1015





For more information please call 1-800-Belden1

See Put-ups and Colors

Description:

Tinned copper conductor, PVC insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring of electronic and electrical equipment.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	1	
Total Number of Conductors	1	
AWG	24	
Stranding	7x32	
Conductor Material	TC - Tinned Copper	

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Insulation Thickness	.030 in.

OVERALL:

Overall Nominal Diameter .088 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

UL AWM Style	1015
UL Rating	600 V, 105°C
CSA Type	TEW
CSA Rating	600 V, 105°C
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	07/01/2005
Other Specification	JQA-F-

FLAME TEST:

UL Flame Test	VW-1	

PLENUM/NON-PLENUM:

Plenum (Y/N)	N	



9924 Hook-up/Lead - UL AWM Style 1015

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9924 001100	24 STR PVC BRN	100	0.7	BROWN	
9924 0011000	24 STR PVC BRN	1000	5	BROWN	P
9924 002100	24 STR PVC RED	100	0.7	RED	
9924 0021000	24 STR PVC RED	1000	5	RED	P
9924 003100	24 STR PVC ORG	100	0.7	ORANGE	
9924 0031000	24 STR PVC ORG	1000	5	ORANGE	P
9924 004100	24 STR PVC YEL	100	0.7	YELLOW	
9924 0041000	24 STR PVC YEL	1000	5	YELLOW	P
9924 005100	24 STR PVC DGRN	100	0.7	GREEN, DARK	
9924 0051000	24 STR PVC DGRN	1000	5	GREEN, DARK	P
9924 0071000	#24 STR PVC VIO	1000	5	VIOLET	P
9924 0081000	#24 STR PVC GRY	1000	5	GRAY	P
9924 009100	24 STR PVC WHT	100	0.7	WHITE	
9924 0091000	24 STR PVC WHT	1000	5	WHITE	P
9924 0095000	#24 STR PVC WHT	5000	25	WHITE	С
9924 010100	24 STR PVC BLK	100	0.7	BLACK	
9924 0101000	24 STR PVC BLK	1000	5	BLACK	P
9924 0105000	#24 STR PVC BLK	5000	25	BLACK	С
9924 013100	24 STR PVC D. BLU	100	0.7	BLUE, DARK	
9924 0131000	24 STR PVC D. BLU	1000	5	BLUE, DARK	P

C = CRATE REEL PUT-UP.

 $P = STRIPE\ COLORS\ ON\ STOCK\ SOLID\ COLORS.\ STRIPING\ ADDER\ OF\ \$8.00/M'\ FOR\ 1\ OR\ 2\ STRIPES.\ 10\ 000'\ MINIMUM\ ORDER\ FOR\ COLOR\ COMBINATION.\ PUT-UP\ WILL\ BE\ SUBJECT\ TO\ TWO\ PIECES\ (+\ OR\ -)\ 10\%\ PER\ SPOOL\ WITH\ A\ MINIMUM\ LENGTH\ OF\ 100'.$

Revision Number: 1 Revision Date: 04-26-2005

Detailed Specifications & Technical Data



9924 Hook-up/Lead - UL AWM Style 1015

© Copyright 2006 Belden, Inc All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described bergin

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Damp; Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product Disclosure is not to be determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.