


Features

- Schottky Brrier Chip
- Low Power Loss,High Efficiency
- Ideally Suited for Automatic Assembly
- Surge Overload Rating to 50A Peak
- Plastic Case Material has UL Flammability Classification Rating 94V-0

Mechanical Data

- Case: MB-S, molded plastic
- Terminals: plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting position: Any
- Marking: type number
- Lead Free: For RoHS / Lead Free Version,



dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics @T_A=25°C unless otherwise specified

Single Phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOL	KMB 22S	KMB 23S	KMB 24S	KMB 245S	KMB 25S	KMB 26S	KMB 28S	KMB 210S	KMB 215S	KMB 220S	KMB 225S	UNITS
Peak Repetitive Reverse Voltage	V _{RRM}	20	30	40	45	50	60	80	100	150	200	250	V
RMS Reverse Voltage	V _{R(RMS)}	14	21	28	31	35	42	56	70	105	140	175	
DC Blocking Voltage	V _{DC}	20	30	40	45	50	60	80	100	150	200	250	
Average Rectified Output Current (Note1) @T _A = 90°C	I _O	2.0											A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	50											A
I ² t Rating for Fusing (t < 8.3ms)	I ² t	5.0											A ² s
Forward Voltage per element @I _F =2.0A	V _{FM}	0.55				0.7		0.85		0.90		0.92	V
Peak Reverse Current @T _A = 25°C At Rated DC Blocking Voltage @T _A = 100°C	I _{RM}	0.1						0.05					mA
		10						5					
Typical Junction Capacitance per leg	C _j	28											pF
Typical Thermal Resistance per leg (Note2)	R _{θJA}	75											°C/W
Operating junction temperature range	T _J	-55 to +150											°C
Operating and Storage Temperature Range	T _{STG}	-55 to +150											°C

Note:

1. Mounted on aluminum substrate PC board with 1.3mm² solder pad.
2. Thermal REsistance From Junction to Ambient

FIG. 1- FORWARD CURRENT DERATING CURVE




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4-TYPICAL REVERSE CHARACTERISTICS




FIG. 5-TYPICAL TRANSIENT THERMAL IMPEDANCE

