

[Search](#)

[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

Pwr Cord, 15A, 100-120V, C19 to 5-15

APC Power Cords , Input: 120V , Input Connections: NEMA 5-15P , Cord Length: 8 feet (2.50 cm) , Output Connections: IEC 320 C19

Part Number : **AP9872**



[Compare Models](#)

[Email Technical Specifications](#)

[Printer Friendly](#)

Additional Information

[Product Overview](#)

[Product Distribution](#)



Technical Specifications

Output

Output Connections	(1) IEC 320 C19
Overload Protection	NO

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Input Connections	NEMA 5-15P 
Cord Length	8.20 feet (2.50 meters)
Acceptable Input Voltage	100-120 VAC
Maximum Line Current per phase	15A
Maximum Input Current per phase	15A
Load Capacity	1800 VA

Physical

Net Weight	0.50 lbs. (0.23 kg)
Maximum Height	3.50 inches (89 mm)
Maximum Width	8.50 inches (216 mm)
Maximum depth	3.50 inches (89 mm)
Shipping Weight	0.65 lbs. (0.30 kg)
Shipping Height	4.00 inches (102 mm)
Shipping Width	12.50 inches (318 mm)
Shipping Depth	4.25 inches (108 mm)

Color	Black
 Environmental	
Operating Environment	0 - 45 °C (32 - 113 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-25 - 65 °C (-13 - 149 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)
 Conformance	
Regulatory Approvals	CSA,UL Listed
Standard Warranty	2 years repair or replace

[Copyright](#) © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#)