

Back-UPS ES 350

APC Back-UPS ES, 350VA/200W, Input 120V/Output 120V, Interface Port USB

Includes: CD with software, Cord Management Straps, Free trial of anti-virus : firewall : email privacy : system recovery and online backup software, USB cable, User Manual, Wall-mounting template



[+] More Images

Part Number : **BE350U**

[Configure Now](#)

- [Compare Models](#)
- [Runtime Chart](#)
- [Email Technical Specifications](#)
- [Printer Friendly](#)

- Additional Information**
- [Product Overview](#)
 - [User Manual & Installation Guides](#)
 - [Product Distribution](#)

Technical Specifications

Output	
Output Power Capacity	200 Watts / 350 VA
Max Configurable Power	200 Watts / 350 VA
Nominal Output Voltage	120V
Output Connections	(3) NEMA 5-15R (Battery Backup) 
	(3) NEMA 5-15R (Surge Protection) 

Input	
Nominal Input Voltage	120V
Input Frequency	60 Hz +/- 1Hz
Input Connections	NEMA 5-15P 
Cord Length	6 feet (1.83 meters)
Input voltage range for main operations	88 - 139V

Batteries & Runtime

Maintenance free sealed Lead Acid battery with

Options:

- [Interface Connections](#)
- [Replacement Battery Cartridges](#)
- [Services](#)
- [Software](#)

General Features:

- i Audible alarms
 - i Automatic self-test
 - i Battery-protected and surge-only outlets
 - i Cold-start capable
 - i Dataline Surge Protection
 - i Hot-swappable batteries
 - i Lifetime data recovery warranty
 - i Power conditioning
 - i Resettable circuit breakers
 - i Safety-agency approved
 - i Transformer-block spaced outlets
- [more details...](#)

Topology: Standby

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	16 hour(s)
Replacement battery cartridge	RBC35
RBC™ Quantity	1
Typical Backup Time at Half Load	9.4 minutes (100 Watts)
Typical Backup Time at Full Load	2.2 minutes (200 Watts)
Runtime Chart	Back-UPS ES

Communications & Management

Interface Port(s)	USB
Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	365 Joules
Dataline protection	RJ-11 Modem/Fax/DSL protection (two wire single line)

Physical

Maximum Height	3.30 inches (84 mm)
Maximum Width	10.90 inches (277 mm)
Maximum depth	6.90 inches (175 mm)
Net Weight	9.20 lbs. (4.18 kg)
Shipping Weight	10.73 lbs. (4.88 kg)
Shipping Height	4.70 inches (119 mm)
Shipping Width	15.00 inches (381 mm)
Shipping Depth	8.90 inches (226 mm)
Master Carton Units	2.00
Master Carton Dimensions (Length x Width x Height)	15.75 X 10.24 X 9.45 inches
Master Carton Weight	21.50 lbs.
Color	Charcoal
Units per Pallet	120.00

Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-10000 feet (0-3000 meters)
Audible noise at 1 meter from surface of unit	40 dBA

 **Conformance**

Regulatory Approvals

cUL Listed,UL Listed

Standard Warranty
