

Back-UPS ES 725 Broadband

APC Back-UPS ES, 725VA/450W, Input 120V/Output 120V, Interface Port USB

Includes: CD with software, Cord Management Straps, Free trial of anti-virus : firewall : email privacy : system recovery and online backup software, USB cable, User Manual

Part Number : **BE725BB**

[Configure Now](#)



[+] More Images

[Compare Models](#)

[Runtime Chart](#)

[Email Technical Specifications](#)

[Printer Friendly](#)

Additional Information



[Product Overview](#)

[User Manual & Installation Guides](#)


[Product Distribution](#)

Technical Specifications

Output

Output Power Capacity	450 Watts / 725 VA
Max Configurable Power	450 Watts / 725 VA
Nominal Output Voltage	120V
Output Connections	<div>(4) NEMA 5-15R (Battery Backup) </div> <div>(4) NEMA 5-15R (Surge Protection) </div>

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NEMA 5-15P 
Cord Length	6 feet (1.83 meters)
Input voltage range for main operations	98 - 132V

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
--------------	--

Options:

- [Interface Connections](#)
- [Replacement Battery Cartridges](#)
- [Services](#)
- [Software](#)

General Features:

- Audible alarms
 - Automatic self-test
 - Battery-protected and surge-only outlets
 - Cold-start capable
 - Dataline Surge Protection
 - Hot-swappable batteries
 - Lifetime data recovery warranty
 - Power conditioning
 - Resettable circuit breakers
 - Safety-agency approved
 - Transformer-block spaced outlets
- [more details....](#)

Topology: Standby

Battery type	suspended electrolyte : leakproof
Typical recharge time	16 hour(s)
Replacement battery cartridge	RBC17
RBC™ Quantity	1
Typical Backup Time at Half Load	14.0 minutes (225 Watts)
Typical Backup Time at Full Load	4.3 minutes (450 Watts)
Runtime Chart	Back-UPS ES

Communications & Management

Interface Port(s)	USB
Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	365 Joules
Dataline protection	RJ-45 Modem/Fax/DSL/10-100 Base-T protection,Co-axial Video / Cable protection

Physical

Maximum Height	4.00 inches (102 mm)
Maximum Width	11.00 inches (279 mm)
Maximum depth	7.10 inches (180 mm)
Net Weight	16.20 lbs. (7.36 kg)
Shipping Weight	17.60 lbs. (8.00 kg)
Shipping Height	7.50 inches (191 mm)
Shipping Width	13.90 inches (353 mm)
Shipping Depth	10.10 inches (257 mm)
Color	Charcoal

Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-10000 feet (0-3000 meters)

Conformance

Regulatory Approvals	cUL Listed,FCC Part 15 Class B,FCC Part 68,UL 1778,UL Listed
Standard Warranty	2 years repair or replace

**The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS.

