



Select Your Country/Region

[Search](#)

[Home](#)[Products](#)[Support](#)[Services](#)[Selectors](#)[How to Buy](#)

Back-UPS CS 350

APC Back-UPS CS, 350VA/210W, Input 120V/Output 120V, Interface Port DB-9 RS-232, USB

Includes: CD with software, Cord Management Straps, USB cable, User Manual

Part Number : **BK350**

[Configure Now](#)



[Compare Models](#)



[Runtime Chart](#)



[Email Technical Specifications](#)



[Printer Friendly](#)

Additional Information

[Product Overview](#)

[User Manual & Installation Guides](#)



[Product Distribution](#)




[+] More Images

Technical Specifications

Output

Output Power Capacity	210 Watts / 350 VA
Max Configurable Power	210 Watts / 350 VA
Nominal Output Voltage	120V
Output Connections	(3) NEMA 5-15R (Battery Backup) 
	(3) NEMA 5-15R (Surge Protection) 

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NEMA 5-15P 
Cord Length	6 feet (1.83 meters)
Input voltage range for main operations	98 - 140V

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	8 hour(s)
Replacement battery cartridge	CURK2 , RBC2 , RBC2J

Options:

- i [Interface Connections](#)
- i [Replacement Battery Cartridges](#)
- i [Services](#)

General Features:

- i Audible alarms
 - i Automatic restart of loads after UPS shutdown
 - i Automatic self-test
 - i Battery replacement without tools
 - i Battery-protected and surge-only outlets
 - i Dataline Surge Protection
 - i Hot-swappable batteries
 - i LED status indicators
 - i Power conditioning
 - i Resettable circuit breakers
 - i Safety-agency approved
 - i Serial Connectivity
 - i Transformer-block spaced outlets
 - i USB connectivity
 - i User-replaceable batteries
- [more details....](#)

Topology: Standby

RBC™ Quantity	1
Typical Backup Time at Half Load	18.1 minutes (105 Watts)
Typical Backup Time at Full Load	4.7 minutes (210 Watts)
Runtime Chart	Back-UPS CS

Communications & Management

Interface Port(s)	DB-9 RS-232,USB
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	480 Joules
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Dataline protection	RJ-45 Modem/Fax protection (two wire single line)

Physical

Maximum Height	6.50 inches (165 mm)
Maximum Width	3.60 inches (91 mm)
Maximum depth	11.20 inches (284 mm)
Net Weight	12.50 lbs. (5.68 kg)
Shipping Weight	14.00 lbs. (6.36 kg)
Shipping Height	10.35 inches (263 mm)
Shipping Width	6.89 inches (175 mm)
Shipping Depth	14.06 inches (357 mm)
Master Carton Units	2.00
Master Carton Weight	29.00 lbs.
Color	Beige
SCC Codes	1073130401629 5
Units per Pallet	80.00

Environmental

Operating Environment	0 - 40 °C (32 - 104 °F)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-15 - 45 °C (5 - 113 °F)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-50000 feet (0-15000 meters)
Audible noise at 1 meter from surface of unit	45 dBA
Online Thermal Dissipation	20 BTU/hr

Conformance

Regulatory Approvals	FCC Part 15 Class B,Industry Canada,UL 1778,cUL Listed
----------------------	--