



BU-00000-\*  
Part # color

\* 0 - Black 5 - Green  
2 - Red 6 - Blue  
4 - Yellow 9 - White

**TEST LEADS**

[1](#) | [2](#) | [3](#) | [4](#) | [5](#) | [6](#) | [7](#) | [8](#) | [9](#) | [10](#) | [11](#) | [12](#) | [13](#) | [14](#) | [15](#) | [16](#) | [17](#) | [18](#) Page 1



[Enlarge](#)

**BU-1149-A-00-\***

**"Mini-Plunger" To Tinned End Wire**

- Mini-Plunger (No. 202) has spring-loaded hook.
- One-piece beryllium copper conductor.
- #20 AWG (41/36), PVC insulated tinned copper wire with 105°C.
- [Product Data Sheet](#)
- [Send us your questions about this product](#)

**BU-1449-E-00-\***

**"Mini-Micro-Plunger" To Tinned End Wire**

- Mini-Micro-Plunger (No. 208) has gold-plated one-piece beryllium copper conductor.
- Nylon stem and cap.
- Stainless steel compression string.
- Attaches to 0.025" (.6mm) dia. and smaller component leads.
- #22 AWG wire (19/34) tinned copper with 105°C PVC insulation.
- [Product Data Sheet](#)
- [Send us your questions about this product](#)



[Enlarge](#)

**BU-1010-A-00-\* "Micro-Plunger Clip"**

**BU-1111-A-00-\* "Mini-Plunger Clip"**

**BU-1212-A-00-\* "Plunger Clip"**

- Three Plunger sizes and five lengths.
- Spring-loaded, beryllium copper conductor.
- #20 AWG wire (41/36) tinned copper with 105°C PVC insulation.
- [Product Data Sheet](#)
- [Send us your questions about this product](#)

**BU-1414-E-00-\***

**"Mini-Micro-Plunger" On Both Ends**

- Gold-plated one-piece beryllium copper conductor, (No. 208).
- Nylon stem and cap.
- Stainless steel compression spring.
- Attaches to 0.025" (.6mm) dia. and smaller component leads.
- #22 AWG wire (19/34) tinned copper with 105°C PVC insulation.
- [Product Data Sheet](#)
- [Send us your questions about this product](#)



[Accessories & Probes](#)|[Kits](#)|[Cross Reference](#)

©1999-2000 Mueller Electric Company. All rights reserved.  
Problems with the site should be reported to the [webmaster](#).