



BU-00000- *
Part # color

* 0 - Black 5 - Green
2 - Red 6 - Blue
4 - Yellow 9 - White

TEST LEADS

[1](#) | [2](#) | [3](#) | [4](#) | [5](#) | [6](#) | [7](#) | [8](#) | [9](#) | [10](#) | [11](#) | [12](#) | [13](#) | [14](#) | [15](#) | [16](#) | [17](#) | [18](#) Page 16



BU-00285

Insulated "Mini-Alligator" Lead Set

- #22 AWG wire, 18" long.
- Jaw opens 1/4" (6.4mm) max.
- [Product Data Sheet](#)
- [Send us your questions about this product](#)

BU-00286

Insulated "Alligator" Lead Set

- #22 AWG wire, 12" long.
- Skin-tight, flexible insulator.
- Jaw opens 7/16" (11.1mm) max.
- [Product Data Sheet](#)
- [Send us your questions about this product](#)



BU-00287

Insulated "Alligator" Lead Set

- #22 AWG wire, 18" long.
- Tinned copper wire.
- Jaw opens 5/16" (7.9mm) max.
- [Product Data Sheet](#)
- [Send us your questions about this product](#)



BU-2929-M-00-*


Unshrouded Banana Plugs On Both Ends-Ultra-Flexible-Silicone

- 413 strands of soft drawn copper inside silicone rubber insulation.
- Nine leaf banana plug construction.
- #18 AWG wire, UL listed to max voltage 3,000V.22 Amp rating.

Compatible with:

- Fluke® 10, 70, and 80 Series DMM
- Series I and II ScopeMeter®
- 860 Series Graphical™ Multimeter
- Hewlett-Packard® HP970A Series
- Tektronix® DMM250 Series
- THM 500 Series

- [Product Data Sheet](#)
- [Send us your questions about this product](#)





BU-5656-B-00-0

Insulated BNC Male—Both Ends

- Insulated, nylon housing.
- Nickel-plated brass center contact.
- Tinned copper wire.
- Coaxial cable RG58 50 ohm.
- [Product Data Sheet](#)
- [Send us your questions about this product](#)

[Contents](#) | [Next](#)

[Home](#) | [Insulated BNCs](#) | [Clips & Insulators](#) | [Insulated Test Accessories](#)
[Accessories & Probes](#) | [Kits](#) | [Cross Reference](#)

©1999-2000 Mueller Electric Company. All rights reserved.
Problems with the site should be reported to the [webmaster](#).