

Product SKU: C5844.41.01

Product Description: C5844, Coaxial Cable, RG59/U Type, 20 AWG Solid Copper Clad Steel, 100% Flexfoil® Bonded +67% Aluminum Braid w/water block, Polyethylene Jacket - Black - 1000 Ft. Reel

Product Category: Electronics - Coaxial Cable - RG 59/U - Black



Product Construction:

- | | |
|------------------|--|
| Conductor: | <ul style="list-style-type: none">• Copper clad steel per ASTM B-869 |
| Insulation/Core: | <ul style="list-style-type: none">• Cellular polyethylene |
| Shield: | <ul style="list-style-type: none">• Aluminum braid• Flexfoil ® shield |
| Jacket: | <ul style="list-style-type: none">• Permaline® polyethylene |

Product Specification:

- | | |
|-------------------------------------|---|
| No. of Conductors: | <ul style="list-style-type: none">• 1 |
| Conductor Size (AWG): | <ul style="list-style-type: none">• 20 |
| Jacket Color: | <ul style="list-style-type: none">• Black |
| Insulation Material (in): | <ul style="list-style-type: none">• Cellular Polyethylene 0.146 |
| Insulation Material (mm): | <ul style="list-style-type: none">• Cellular Polyethylene 3.71 |
| Shield Coverage Nominal Shield DCR: | <ul style="list-style-type: none">• 100% Flexfoil® Bonded +67% Aluminum Braid w/water block 9.7 Ohm/M |
| Nominal Outside Diameter (in): | <ul style="list-style-type: none">• 0.242 |
| Nominal Outside Diameter (mm): | <ul style="list-style-type: none">• 6.15 |

Nominal Capacitance (pF/ft):	16.20
Nominal Capacitance (pF/m):	53.15
Velocity of Propagation %:	85
Nominal Impedance Ohm:	75
Nominal Attenuation MHz/dB per 100 ft:	200/3.70 10/1.20 1/0.60 50/1.95 100/2.70 500/5.70 1000/8.12
Standard Packaging:	1000' Non-returnable Wood Reels
Standard Package Quantity:	1
UPC #:	079407742134
Footnote:	Moistureguard Direct Burial, Flooded
Put-up:	1000
SCC-14:	50079407742133
Cube:	1518.6875
Weight Per Unit of Measure:	.02
ColorOption:	Black

Product Information:

Applications:

- Citizen band radio
- Direct burial
- Local Area Network (LAN)
- MATV
- Monitor/VDT Display
- Suitable for RF signal transmission

Packaging:

- 1000 foot (305 m) Pull-Pac Â® Cartons
- 1000' (305 m) Reels
- Other put-ups available- consult Customer Service

Technical Specifications

[Unit Conversion Factors](#)

[Cable Design Equations - Balanced Pair](#)

[Insulation and Jacket Properties](#)

[Temperature Conversion Chart](#)

[Decimal and Unit Conversion Factors](#)

[Cable Design Equations - Braid Shield](#)

[AWG Conductor Chart](#)

[Conduit Capacity Chart](#)

[Cable Design Equations - Coaxial Cable](#)

[Engineering Prefixes](#)

[Coax Connector Cross Reference](#)

[Glossary](#)

**CAROL
BRAND**