




Bridge Rectifiers, Controlled Avalanche*

Single Phase, Full Wave

1.5 to 35 Amperes

200 to 800 Volts

I _O (AMPS)	1.5	2.0	3.0	6.0	10
@T _A (°C)	50	55	2.0 @ 25	50	
@T _C (°C)			3.0 @ 50	100	100
I _{FSM} (AMPS)		60	50	150	150
CASE	 CASE A		 CASE C	 CASE CM	
V _{RRM} (VOLTS)					
200	CBR1A-020	CBR2A-020	CBR3A-P020	CBR6A-020	CBR10A-J020
400	CBR1A-040	CBR2A-040	CBR3A-P040	CBR6A-040	CBR10A-J040
600	CBR1A-060	CBR2A-060	CBR3A-P060	CBR6A-060	CBR10A-J060
800	CBR1A-080	CBR2A-080	CBR3A-P080	CBR6A-080	CBR10A-J080
V _F MAX @ I _F	1.0V @ 1.0A	1.1V @ 2.0A	1.1V @ 1.5A	1.1V @ 3.0A	1.2V @ 5.0A
I _R MAX @ V _{RRM}	10μA	10μA	10μA	10μA	10μA

*AVALANCHE BREAKDOWN VOLTAGE		
V _{RRM}	MIN	MAX
200V	250	700
400V	450	900
600V	650	1100
800V	850	1300