

Molded S-Video Cable, Male / Male, 10.0 ft

Features for this product

- Length of cable 10 feet
- Dual coaxial cables support high quality video signal transmission
- Gold plated contacts reduce signal loss
- Molded strain reliefs produce a durable cable assembly
- Available from stock in 10 lengths ranging from 1 to 50 feet



These high quality S-Video cable assemblies utilize dual 75 Ohm coaxial cables for unmatched video signal transmission. The molded strain relief Mini Din 4 male connectors with gold plated contacts assure distortion free performance. We typically carry these exceptional quality cable assemblies in stock in 10 handy lengths from 1 to 50 ft.

Details for this Monitor, Video product

L-com Item #	CCD234MM-10
Manufacturer	L-com
UPC #	822335006997
RoHS Status	Not Compliant At This Time

**Tip****What is S-Video (S-VHS)?**

The term S-Video is derived from the way the video signal is transmitted. In S-Video the signal is separated into two components hence the term Separate Video or S-Video. Two 75 Ohm coaxial cables and a Mini DIN 4 connector are utilized to transmit the two component signals. One of the coaxial cables carries the Luminance Signal (brightness or Y component) while the second 75 Ohm coaxial cable carries the Chrominance Signal (color or C component). By separating the video signal into two components a better quality picture is produced than composite video that utilizes one coaxial cable to transmit both signals. The term S-VHS is an acronym for Super-Video Home System.

SVHS (S-Video) Jack**R1088 Cable Specification**

Item #	Description
Molded S-Video Cable Assemblies, 75 Ohm Dual Coaxial in Single Jacket	
CCD234MM-1	Molded Mini DIN 4 Male / Male, 1.0 ft
CCD234MM-2	Molded Mini DIN 4 Male / Male, 2.0 ft
CCD234MM-3	Molded Mini DIN 4 Male / Male, 3.0 ft
CCD234MM-5	Molded Mini DIN 4 Male / Male, 5.0 ft
CCD234MM-7.5	Molded Mini DIN 4 Male / Male, 7.5 ft
CCD234MM-10	Molded Mini DIN 4 Male / Male, 10.0 ft
CCD234MM-20	Molded Mini DIN 4 Male / Male, 20.0 ft
CCD234MM-30	Molded Mini DIN 4 Male / Male, 30.0 ft
CCD234MM-40	Molded Mini DIN 4 Male / Male, 40.0 ft
CCD234MM-50	Molded Mini DIN 4 Male / Male, 50.0 ft
CCD234MF-1	Molded Mini DIN 4 Male / Female, 1.0 ft
CCD234MF-2	Molded Mini DIN 4 Male / Female, 2.0 ft
CCD234MF-3	Molded Mini DIN 4 Male / Female, 3.0 ft
CCD234MF-5	Molded Mini DIN 4 Male / Female, 5.0 ft
CCD234MF-7.5	Molded Mini DIN 4 Male / Female, 7.5 ft
CCD234MF-10	Molded Mini DIN 4 Male / Female, 10.0 ft
CCD234MF-20	Molded Mini DIN 4 Male / Female, 20.0 ft
Assembled S-Video Cable Assemblies, 75 Ohm Dual Coaxial in Single Jacket	
CCD244MM-1	Assembled Mini DIN 4 Male / Male, 1.0 ft
CCD244MM-2	Assembled Mini DIN 4 Male / Male, 2.0 ft
CCD244MM-3	Assembled Mini DIN 4 Male / Male, 3.0 ft
CCD244MM-5	Assembled Mini DIN 4 Male / Male, 5.0 ft
CCD244MM-7.5	Assembled Mini DIN 4 Male / Male, 7.5 ft
CCD244MM-10	Assembled Mini DIN 4 Male / Male, 10.0 ft
CCD244MM-20	Assembled Mini DIN 4 Male / Male, 20.0 ft
CCD244MF-1	Assembled Mini DIN 4 Male / Female, 1.0 ft
CCD244MF-2	Assembled Mini DIN 4 Male / Female, 2.0 ft
CCD244MF-3	Assembled Mini DIN 4 Male / Female, 3.0 ft
CCD244MF-5	Assembled Mini DIN 4 Male / Female, 5.0 ft
CCD244MF-7.5	Assembled Mini DIN 4 Male / Female, 7.5 ft
CCD244MF-10	Assembled Mini DIN 4 Male / Female, 10.0 ft
CCD244MF-20	Assembled Mini DIN 4 Male / Female, 20.0 ft
Assembled S-Video Cable Assemblies - Molded Dual RCA-M, 75 Ohm Dual Coaxial Breakout Cable	
CCD244MR-1	Assembled Mini DIN 4 Male / Dual RCA Male, 1.0 ft
CCD244MR-2	Assembled Mini DIN 4 Male / Dual RCA Male, 2.0 ft
CCD244MR-3	Assembled Mini DIN 4 Male / Dual RCA Male, 3.0 ft
CCD244MR-5	Assembled Mini DIN 4 Male / Dual RCA Male, 5.0 ft
CCD244MR-7.5	Assembled Mini DIN 4 Male / Dual RCA Male, 7.5 ft
CCD244MR-10	Assembled Mini DIN 4 Male / Dual RCA Male, 10.0 ft
CCD244MR-20	Assembled Mini DIN 4 Male / Dual RCA Male, 20.0 ft
Assembled S-Video Cable Assemblies - Molded Dual BNC-M, 75 Ohm Dual Coaxial Breakout Cable	
CCD244MB-1	Assembled Mini DIN 4 Male / Dual BNC Male, 1.0 ft
CCD244MB-2	Assembled Mini DIN 4 Male / Dual BNC Male, 2.0 ft
CCD244MB-3	Assembled Mini DIN 4 Male / Dual BNC Male, 3.0 ft
CCD244MB-5	Assembled Mini DIN 4 Male / Dual BNC Male, 5.0 ft
CCD244MB-7.5	Assembled Mini DIN 4 Male / Dual BNC Male, 7.5 ft
CCD244MB-10	Assembled Mini DIN 4 Male / Dual BNC Male, 10.0 ft
CCD244MB-20	Assembled Mini DIN 4 Male / Dual BNC Male, 20.0 ft
Assembled S-Video to Single Composite RCA Cable Assemblies	
CCD144MR-2	Assembled Mini DIN 4 Male / Single RCA Male, 2.0 ft
CCD144MR-6	Assembled Mini DIN 4 Male / Single RCA Male, 6.0 ft
CCD144MR-10	Assembled Mini DIN 4 Male / Single RCA Male, 10.0 ft
CCD144MR-15	Assembled Mini DIN 4 Male / Single RCA Male, 15.0 ft
CCD144MR-20	Assembled Mini DIN 4 Male / Single RCA Male, 20.0 ft
CCD144MR-25	Assembled Mini DIN 4 Male / Single RCA Male, 25.0 ft

These cables combine the S-Video Mini DIN 4 connector found on SVHS with the single RCA connector used for composite video allowing the conversion from S-Video transmission to composite video.