

# IEC Appliance Connector C8 with Line Switch 1-pole



CMF1

C8



70° C

### Description

- Panel Mount:
- Screw-on mounting on PCB, from top or bottom
- 2 Functions
- Inlet Protection class II, Line switch 1-pole
- For PCB mounting
- Alternative: polarized version or protection class I CMF2; CMF3













#### Characteristics

- Easy mounting with center bolt and snapper or srewed on PCB or housing
- Electrical connection done on the PCB
- Bi-positioning of the switch from left or right side, Standard CMF with switch on right side
- With or without rear-side insulation cover
- Qualified for use in equipment according IEC/EN 60950

#### Other versions on request

- Line switch with other rocker marking
- Line switch on left of inlet

#### Weblinks


Approvals: http://www.schurter.com/approvals RoHS: http://www.schurter.com/rohs

Technical Data			
Ratings IEC	2.5 A / 250 VAC; 50 Hz		
Ratings UL/CSA	2.5 A / 125 VAC; 60 Hz		
Dielectric Strength	> 2.3 kVAC between L-N		
	> 2.8 kVAC between L/N-PE		
	(1 min/50 Hz)		
Allowable Operation Temp.	-25 °C to 70 °C		
Degree of Protection	from front side IP 40 acc. to IEC 60529		
Protection Class	Suitable for appliances with protection		
	class II acc. to IEC 61140		
Terminal	PCB 1.6 mm		
Material: Housing	Thermoplastic, black, UL 94V-0		

Appliance-Inlet /-Outlet	C8 acc. to IEC/EN 60320-1,	
	UL 498, CSA C22.2 no. 42 (for cold con-	
	dition) pin-temperature 70 °C, 2.5 A, Pro-	
	tection class II	
Line Switch	Rocker switch 1 pole, non-illuminated,	
	acc. to IEC 61058-1	
	Technical details	

Dimensions

Length 53.3 mm





with insulation cover

The size of the mounting cut-out can be selected as required.

Fixation on PCB or housing from below

Fixation on PCB or housing from above






1) self tapping screw

1) self tapping screw

# Drilling diagrams

CMF1 and CMF2 (C8)



d1 = 6.2 mm mounting from above d1 = 3.6 mm mounting from below

PC Board 1.6 mm

Dimensions without tolerance:<TAB/>

 $\leq 15 = \pm 0.05 / > 15 = \pm 0.10$ 

### Variants

Standard CMF with switch on right side

Appliance-inlet	Mounting side	Cover	Ground terminal	Ground terminal direction	Order Number
C8	from below		-	-	CMF1.1031.12
C8	from below	•	-	-	CMF1.1131.12
C8	from top		-	-	CMF1.1011.12
C8	from top	•	-	-	CMF1.1111.12

Packaging unit

50 Pcs