

**tyco****Electronics**

a vital part of your world

[Products](#) [Catalog](#) [Brands](#) [Industries](#) [Commerce](#) [Supplier](#) [Contact Us](#) [About](#) [Home](#)

English ...

Search by: [Text](#) | [Part Number](#)[Tips](#) ▶

Text Search:

Friday, 13 January, 2006

## CATALOG

## → Cross Reference

[Competitive Products](#)[Military Spec P/Ns](#)[Tyco Brand P/Ns](#)


- [Part Number Search](#)
- [Document Search](#)
- [Product Type Search](#)
- [Product Family Search](#)
- [Alphabetical Search](#)
- [RoHS/ELV Compliance & Alternates](#)
- [CAD Model Search](#)
- [Brand Search](#)
- [Tool Search](#)
- [Multiple Part Comparison](#)
- [Lead Free Solutions](#)
- [Help/Glossary](#)

[Home](#)

e-bulletin newsletter

**SUBSCRIBE NOW!**

click here

**Solder Sleeve Terminators****➔ Cable Terminations****Raychem** CWT-4174-W122-5/9  [Active](#)

Not ELV or RoHS Compliant

**(Corporate P/N: 644529-000)**[Search for Compliant \(RoHS/ELV\)](#)[Alternates](#)[Search for Parts](#)

Document links for this part cannot be displayed. Your browser does not support inline frames or is currently configured not to display inline frames. Inline frames are supported in both Internet Explorer 5 and Netscape 6, as well as all later versions of these browsers.

**Related Part Information**

General Information	eCommerce	Related Part Information
<ul style="list-style-type: none"> <li>➤ <a href="#">General Info</a></li> <li>➤ <a href="#">Sales Info</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Pricing &amp; Availability</a></li> </ul>	<ul style="list-style-type: none"> <li>➤ <a href="#">Tooling</a></li> </ul>

**Photos & Line Drawings** - The photographs and/or line drawings are representative images of a product for viewing purposes only.

[Product View](#)[Product View](#)**Searchable Features:**

<b>Brand:</b>	Raychem
<b><a href="#">RoHS/ELV Compliance:</a></b>	Not ELV/RoHS compliant
<b><a href="#">Lead Free Solder Processes:</a></b>	Not relevant for lead free process
<b>Terminate To:</b>	Coaxial Cable
<b>Coaxial Cable Type (RG/U or Mfg.):</b>	174
<b>Jacket Outer Diameter (mm [in]):</b>	1.30 [0.051]
<b>Dielectric O.D. Max. (mm [in]):</b>	0.80 – 2.30 [0.032 – 0.091]
<b>Preinstalled Lead Wire Size (mm² [AWG]):</b>	0.38 [22]
<b>Preinstalled Lead Stranding:</b>	Stranded
<b>Cable Temperature Rating (°C):</b>	85
<b>Cable Shield Material:</b>	Copper, Tin

**Other Properties:**

<b>Operating Temperature (Max.) (°C):</b>	125
<b>Preinstalled Lead Type:</b>	XL Polyethylene
<b>Preinstalled Lead Plating:</b>	Tin