


CWT-9-W122-5 Product Details



CWT-9-W122-5

TE Internal Number: 486085-000



[Active](#)

Shield Terminators

[Not EU RoHS or ELV Compliant](#)

Product Highlights:

- Shield Terminator
- Terminator Type = Solder Sleeve
- Fluid Resistance = Splash Protection
- Cable Temperature Rating = 85 °C
- Jacket Outer Diameter = 8.70 mm

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information	
Product Drawings: • Solder Sleeve Terminator with Pre-installed Lead (PDF, English) Catalog Pages/Data Sheets: • None Available Product Specifications: • None Available Application Specifications: • None Available Instruction Sheets: • None Available CAD Files: • None Available	Additional Information: • Product Line Information Related Products: • Tooling
List all Documents	

Product Features (Please use the Product Drawing for all design activity)	
Product Type Features: • Product Type = Shield Terminator Mechanical Attachment: • Inside Diameter (mm [in]) = 8.70 [0.340] Body Related Features: • Terminator Type = Solder Sleeve • Fluid Resistance = Splash Protection • Jacket Outer Diameter (mm [in]) = 8.70 [0.340] • Preinstalled Lead Plating = Tin Housing Related Features: • Shield O.D. (Min.) (mm [in]) = 4.20 [0.165] • Preinstalled Lead = With • Preinstalled Lead Wire Size (mm² [AWG]) = 0.38 [22] • MIL or NAS Specification (MIL-S-83519) (NAS 1747) = No • Preinstalled Lead Type = XL Polyethylene • Preinstalled Lead Stranding = Stranded • Preinstalled Lead Color = Green • Length (Max.) (mm [in]) = 35.50 [1.400]	Configuration Related Features: • Temperature Indication System = Without Industry Standards: • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not relevant for lead free process Conditions for Usage: • Cable Temperature Rating (°C) = 85 • Operating Temperature (Max.) (°C) = 125 Other: • Brand = Raychem