

# GPS Chip Set for Mobile, Navigation and Multimedia Applications

Atmel's chip set for highly optimized low-power GPS modules is highly integrated, thus enabling drastic board space reduction. Comprising an RF receiver IC, a baseband IC and an LNA, it performs a complete GPS receiver optimized for mobile applications, but can also be used for in-vehicle navigation systems. Chip set and GPS modules are a joint development of Atmel (providing the RF IC/digital IC design know-how) and u-blox, providing the GPS system/software know-how.



## The GPS Chip Set


- Offers Excellent Navigation Accuracy
- Enables Fast Time-to-first-fix
- Is Optimized for Reliable Operation Under Mobile Phone Reception Conditions
- Guarantees Extremely Low Power Consumption (< 100 mW @ 1fix/s)
- Enables Small Form Factors (Required Board Size < 400 mm<sup>2</sup>)
- Significantly Reduces BOM and System Costs
- Supports Network-assisted GPS (NA-GPS)

## Portable Applications

- Mobile Tracking for All Mobile Phones
- Mobile Tracking for PDAs
- Sports and Recreation (i.e. Outdoor)
- Watches

## Automotive Applications

- In-vehicle Navigation
- Fleet Management
- Freight Tracking



## Corporate Headquarters

2325 Orchard Parkway  
San Jose, CA 95131, USA  
Tel.: (1) 408 441-0311  
Fax: (1) 408 487-2600

## Europe

Atmel Sarl  
Route des Arsenaux 41  
Case Postale 80  
CH-1705 Fribourg  
Switzerland  
Tel.: (41) 26-426-5555  
Fax: (41) 26-426-5500

## Asia

Room 1219  
Chinachem Golden Plaza  
77 Mody Road Tsimshatsui  
East Kowloon  
Hong Kong  
Tel.: (852) 2721-9778  
Fax: (852) 2722-1369

## Japan

9F, Tonetsu Shinkawa Bldg.  
1-24-8 Shinkawa  
Chuo-ku, Tokyo 104-0033  
Japan  
Tel.: (81) 3-3523-3551  
Fax: (81) 3-3523-7581

## Product Contact

Theresienstrasse 2  
P.O.B. 3535  
D-74025 Heilbronn  
Germany  
Tel.: (49) 71 31-67-0  
Fax: (49) 71 31-67-2340

## E-mail

literature@atmel.com

## Web Site

<http://www.atmel.com>



© Atmel Corporation 2003.

Atmel Corporation makes no warranty for the use of its products, other than those expressly contained in the Company's standard warranty which is detailed in Atmel's Terms and Conditions located on the Company's web site. The Company assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of Atmel are granted by the Company in connection with the sale of Atmel products, expressly or by implication. Atmel's products are not authorized for use as critical components in life support devices or systems.

Atmel® is a registered trademark of Atmel Corporation. ARM7TDMI® is a registered trademark of ARM Limited. Other terms and product names may be trademarks of others.

Rev.: 4606C-GPS-01/03/10M

## GPS RF Receiver IC ATR0600

- Extremely Low Power Consumption (50 mW typically) Due to Single IF Front End Concept
- Excellent Blocking Performance of Nearby GSM Frequencies
- High Integration Level (VCO Tank, Loop Filter and Gain-control Filter on Chip, only one External Low-cost LC Filter Necessary)
- RF LNA Noise Figure < 1.2 dB
- 1.5-Bit ADC on Chip
- UHF6 Technology
- 28 QFN Package (5 x 5 mm)

## LNA ATR0610

- Excellent Noise Figure ( $N_{fmin} < 1.6$  dB)
- Very Low Power Design (< 10 mW)
- High Gain (> 16 dB)
- Integrated Power-up Control
- Integrated Output Match
- SiGe Technology
- Small PLLP6 Package (1.6 x 2 mm)


## GPS Baseband IC ATR0620

- High-performance GPS Engine Using a 16-channel GPS Core Driven by an ARM7TDMI® Core on Chip
- Various Interfaces (3 USARTs, SPI Interface, GPIO) for Flexible System Integration
- Low-power Management Enables Maximum Efficiency
- ROM/SRAM on Chip
- 2.3 - 3.6 V or 1.8 V Supply Voltage
- LDO (Low Drop Output) on Chip
- 0.21-µm CMOS Technology
- 100 BGA Package (9 x 9 mm)

## GPS Performance

Receiver Type	16 Channels, 8192 Parallel Search Bins, L1 Frequency, C/A Code	
Maximum Update Rate	4 Hz	
Accuracy	Position	3 m CEP
Start-up Times	Hot Start	2.5 s
	Warm Start	33 s
	Cold Start	41 s
Signal Reacquisition	< 1 s	
Dynamics	< 4 g	

CEP = Circular Error Probability



## Support

For easy design-in, a complete application-specific support package including extensive GPS software and a highly sophisticated low-power reference design for time-efficient GPS platform development is available.