



ELECTRONICS, INC.
44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089

NTE961 Linear Integrated Circuit Voltage Regulator, Negative, 5V, 1A

Description:

The NTE961 voltage regulator employs current limiting, thermal shutdown, and safe-area compensation which makes it remarkably rugged under most operating conditions. With adequate heat-sinking they can deliver output currents in excess of 1.0 amperes.

Features:

- No External Components Required
- Internal Thermal Overload Protection
- Internal Short-Circuit Current Limiting
- Output Transistor Safe-Area Compensation

Absolute Maximum Ratings:

Input Voltage, V_{IN}	−35V
Input-Output Differential	25V
Internal Power Dissipation (Note 1), P_D	Internally Limited
Operating Junction Temperature Range, T_J	0° to +125°C
Storage Temperature Range, T_{stg}	−65° to +150°C
Lead Temperature (Soldering, 10sec.), T_L	+230°C

Note 1. For calculations of junction temperature rise due to power dissipation, thermal resistance junction to ambient (Θ_{JA}) is 50°C/W (no heat sink) and 5°C/W (infinite heat sink).

Electrical Characteristics: ($V_{OUT} = 5V$, $V_{IN} = -10V$, $0^\circ C \leq T_J \leq +125^\circ C$, $I_O = 500mA$, $C_{IN} = 2.2\mu F$, $C_{OUT} = 1\mu F$, $P_D \leq 1.5W$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V_O	$T_J = +25^\circ C$,	−4.8	−5.0	−5.2	V
		$5mA \leq I_O \leq 1A$, $P \leq 15W$	−4.75	—	−5.25	V
			$(-20 \leq V_{IN} \leq -7)$			V



Electrical Characteristics Cont'd): ($V_{OUT} = 5V$, $V_{IN} = -10V$, $0^{\circ}C \leq T_J \leq +125^{\circ}C$, $I_O = 500mA$, $C_{IN} = 2.2\mu F$, $C_{OUT} = 1\mu F$, $P_D \leq 1.5W$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Line Regulation	ΔV_O	$T_J = +25^{\circ}C$, Note 2	–	8	50	mV
			$(-25 \leq V_{IN} \leq -7)$			V
			–	2	15	mV
			$(-12 \leq V_{IN} \leq -8)$			V
Load Regulation	ΔV_O	$T_J = +25^{\circ}C$	–	15	100	mV
		Note 2	–	5	50	mV
Quiescent Current	I_Q	$T_J = +25^{\circ}C$	–	1	2	mA
Quiescent Current Change	ΔI_Q	With Line	–	–	0.5	mA
			$(-25 \leq V_{IN} \leq -7)$			V
		With Load, $5mA \leq I_O \leq 1A$	–	–	0.5	mA
Output Noise Voltage	V_n	$T_A = +25^{\circ}C$, $10Hz \leq f \leq 100Hz$	–	125	–	μV
Ripple Rejection		$f = 120Hz$	54	66	–	dB
			$(-18 \leq V_{IN} \leq -8)$			V
Dropout Voltage		$T_J = +25^{\circ}C$, $I_O = 1A$	–	1.1	–	V
Peak Output Current	I_{OMAX}	$T_J = +25^{\circ}C$	–	2.2	–	A
Average Temperature Coefficient of Output Voltage		$I_O = 5mA$, $0^{\circ}C \leq T_J \leq 100^{\circ}C$	–	0.4	–	$mV/^{\circ}C$

Note 2. Regulation is measured at a constant junction temperature by pulse testing with a low duty cycle. Changes in output voltage due to heating effects must be taken into account.

