





F1X2LG6-A



- Choose from 29 sizes of *PANDUIT* Type F Wiring Duct from 0.5" x 0.5" up to 4.0" x 5.0". Used for general purpose control panel wiring in communication closets. Ideal for use with high-density terminal blocks. The non-slip cover conceals all wiring and is easy to install. The duct and cover form a flush sidewall providing increased capacity and improved aesthetics.
- **Specifications**
 - Made of lead-free PVC
 - UL Recognized continuous use temperature: 50°C (122°F)
 - UL94 Flammability Rating of V-0
 - Conforms with NFPA 79-2002 section 14.3.1 requirement for flame retardant material
 - Available in Light Gray and White
 - Provided with mounting holes
- **Features and Benefits**
 - Narrow finger/slot design allows further fanning of wires for neater wire management in high-density control panels
 - *PANDUIT* exclusive rounded edges protects hands and wiring/cabling from abrasion
 - Non-slip cover stays in place during shipment, vibration and when in a vertical orientation, eliminating rework
 - Flush cover design holds 10-12% more wires than traditional duct designs
 - Double scoreline allows quick modification for larger cabling bundles saving installation time leading to a lower installed cost
 - Specially formulated lead-free material eliminates health concerns associated with PVC that contains lead
 - Double restricted slot design retains wire in slot for fast, easy wire installation or removal
- Base and cover sold separately.

■ Part Number	F1X2LG6-A
■ RoHS Compliancy Status	Compliant
■ Part Description	Narrow finger, slotted wiring duct.
■ Material	Lead-Free PVC
■ Color	Light Gray
■ CSA Certified	Yes
■ UL Recognized (File No. E147128)	Yes
■ Length (ft.)	6
■ Adhesive Mounting Tape	Yes
■ CE Marking	Yes
■ Duct Size W x H (In.)	1.26 x 2.12
■ Duct Size W x H (mm)	32.0 x 53.8
■ Mounting Method	Standard Mountig Holes with Adhesive
■ Pricing Description	Slotted Duct,PVC,1"X2"X6',Adh.,LGray

■ Slot Width (In.)	.20
■ Slot Width (mm)	5.0
■ Cover Part Number	C1LG6
■ Min. Order UOM	FT
■ Min. Order Qty.	6
■ BOM Qty. (# of Pkgs.)	



A **G**

NOTE.

1. ALL DIMENSIONS ARE REFERENCE ONLY.
2. DIMENSIONS IN PARENTHESES ARE METRIC.
3. THE ** DENOTE COLOR.
4. DUCT AND COVER ARE AVAILABLE IN 6 FT [1828.8] LENGTH

				CAD FILENAME/LAYERS				DI1000BZ_DC/OIC	
				PANDUIT				CORP. TINLEY PARK, ILLINOIS	
				WIRING DUCT - TYPE F WITH COVER				1 X 2	
				MARKETING DRAWING					
				DRAWN BY		DATE		SCALE	
				JCST		1-22-02		FULL	
				MAT'L:		PVC		DRAWING NO.	
				CHECKED BY		JGG		36897-675	
				REV		DATE		BY	
				CHK		DESCRIPTION		DWG	
								B	
								SIZE	