



Product Search

- [Product Home](#)
- [Features](#)
- [Specifications](#)
- [Models, Pricing, Options, Accessories](#)

- [Manuals](#)
- [Product Registration](#)

Digital Multimeters >

Fluke 12 Digital Multimeter

Voltage DC	Range and Resolution:4000 mV*, 4.000V, 40.00V, 400V, 600V Best Accuracy: Model 10 $\pm(1.5\%+1)$ Model 11 $\pm(0.9\%+1)$ Model 12 $\pm(0.9\%+1)$
Voltage AC	Range and Resolution:4000 mV, 4.000V, 40.00V, 400V, 600V Model 10 $\pm(2.9\%+3)$ Best Accuracy: Model 11 $\pm(1.9\%+3)$ Model 12 $\pm(1.9\%+3)$
Resistance	Range and Resolution:400.0 Ω , 4.000 k Ω , 40.00 k Ω , 400.0 k Ω , 4.000 M Ω , 40.00 M Ω Best Accuracy: Model 10 $\pm(1.5\%+1)$ Model 11 $\pm(0.9\%+1)$ Model 12 $\pm(0.9\%+1)$
Capacitance	Range and Resolution:1.000 μ F, 10.00 μ F, 100.0 μ F, 1000 μ F, 10,000 μ F Best Accuracy: Model 10 N/A Model 11 $\pm(1.9\%+2)$ Model 12 $\pm(1.9\%+2)$
Note	*Available in manual mode. Use this range with accessories.

Size	142.3 mm L x 70.5 mm W x 34.6 mm
Weight	286g
Warranty	Three years, one year guaranteed calibration
Battery life	Alkaline: 650 hours continuous Carbon-zinc:450 hours continuous