



GOOD-ARK

FR601G THRU FR607G

GLASS PASSIVATED JUNCTION FAST SWITCHING RECTIFIER


Reverse Voltage - 50 to 1000 Volts

Forward Current - 6.0 Amperes

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0 utilizing Flame retardant epoxy molding compound
- Glass passivated junction in R-6 package
- 6.0 ampere operation at $T_A=75^\circ\text{C}$ with no thermal runaway
- Fast switching for high efficiency

R-6



Mechanical Data

- **Case:** Molded plastic, R-6
- **Terminals:** Axial leads, solderable per MIL-STD-202, method 208
- **Polarity:** Band denotes cathode
- **Mounting Position:** Any
- **Weight:** 0.074 ounce, 2.105 grams

DIMENSIONS					
DIM	inches		mm		Note
	Min.	Max.	Min.	Max.	
A	0.339	0.358	8.6	9.1	
B	0.339	0.358	8.6	9.1	φ
C	0.047	0.052	1.2	1.3	φ
D	1.000	-	25.40	-	

Maximum Ratings and Electrical Characteristics @25°C unless otherwise specified

	Symbols	FR 601G	FR 602G	FR 603G	FR 604G	FR 605G	FR 606G	FR 607G	Units
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Average forward rectified current at $T_A=75^{\circ}\text{C}$	$I_{(AV)}$	6.0							Amps
Peak forward surge current 8.3ms single half sine-wave	I_{FSM}	300.0							Amps
Maximum instantaneous forward voltage $I_{FM}=6.0\text{A}$; $T_A=25^{\circ}\text{C}$ (Note 1)	V_F	1.3							Volts
Maximum DC reverse current at rated DC blocking voltage $T_A=25^{\circ}\text{C}$ $T_A=55^{\circ}\text{C}$	I_R	10.0 150.0							$\mu\text{ A}$
Maximum reverse recovery time at $I_F=0.5\text{A}$, $I_R=1.0\text{A}$, $I_{rr}=0.25\text{A}$	T_{rr}	150				250	500		nS
Typical junction capacitance Measured at 1.0MHz, $V_R=4.0\text{V}$	C_j	150							p F
Operating and storage temperature range	T_J, T_{STG}	-65 to +150							$^{\circ}\text{C}$

Note:

(1) Pulse test: Pulse width 300uSec, Duty cycle 1%



RATINGS AND CHARACTERISTIC CURVES

Figure 1
Typical Forward Characteristics




Figure 2
Forward Derating Curve






Figure 3
Junction Capacitance



RATINGS AND CHARACTERISTIC CURVES



Peak Forward Surge Current - Amperes *versus*
Number Of Cycles At 60Hz - Cycles

Figure 5
Reverse Recovery Time Characteristic And Test Circuit Diagram

