


SKiiP 342GDL120-4DU



7-pack - integrated intelligent Power System

Power section - brake chopper

SKiiP 342GDL120-4DU


Features

- SKiiP technology inside
- CAL diode technology
- Integrated current sensor
- Integrated temperature sensor
- Integrated heat sink
- IEC 60721-3-3 (humidity) class 3K3/IE32 (SKiiP® 2 System)
- IEC 60068-1 (climate) 40/125/56
- UL recognized file no. E63532


1) with assembly of suitable MKP capacitor per terminal (SEMIKRON type is recommended)

Absolute Maximum Ratings		$T_s = 25\text{ °C}$ unless otherwise specified	
Symbol	Conditions	Values	Units
IGBT			
V_{CES}	Operating DC link voltage	1200	V
$V_{CC}^{(1)}$		900	V
V_{GES}		± 20	V
I_C	$T_s = 25\text{ (70) °C}$	300 (225)	A
Inverse diode			
$I_F = -I_C$	$T_s = 25\text{ (70) °C}$	300 (225)	A
I_{FSM}	$T_j = 150\text{ °C}$, $t_p = 10\text{ ms}$; sin.	2160	A
I^2t (Diode)	Diode, $T_j = 150\text{ °C}$, 10 ms	23	kA ² s
T_j , (T_{stg})		- 40 (- 25) ... + 150 (125)	°C
V_{isol}	AC, 1 min. (mainterminals to heat sink)	3000	V


Characteristics		$T_s = 25\text{ °C}$ unless otherwise specified						
Symbol	Conditions	min.	typ.	max.	Units			
IGBT								
V_{CEsat}	$I_C = 250\text{ A}$, $T_j = 25\text{ (125) °C}$		2,6 (3,1)	3,1	V			
V_{CEO}	$T_j = 25\text{ (125) °C}$		1,2 (1,3)	1,5 (1,6)	V			
r_{CE}	$T_j = 25\text{ (125) °C}$		5,3 (7)	6,3 (8,1)	mΩ			
I_{CES}	$V_{GE} = 0\text{ V}$, $V_{CE} = V_{CES}$, $T_j = 25\text{ (125) °C}$		(15)	0,4	mA			
$E_{on} + E_{off}$	$I_C = 250\text{ A}$, $V_{CC} = 600\text{ V}$ $T_j = 125\text{ °C}$, $V_{CC} = 900\text{ V}$			75 132	mJ mJ			
$R_{CC'} + EE'$	terminal chip, $T_j = 125\text{ °C}$		0,5		mΩ			
L_{CE}	top, bottom		15		nH			
C_{CHC}	per phase, AC-side		1,4		nF			
Inverse diode								
$V_F = V_{EC}$	$I_F = 250\text{ A}$, $T_j = 25\text{ (125) °C}$		2,1 (2)	2,6	V			
V_{TO}	$T_j = 25\text{ (125) °C}$		1,3 (1)	1,4 (1,1)	V			
r_T	$T_j = 25\text{ (125) °C}$		3,3 (4)	4,5 (5,2)	mΩ			
E_{rr}	$I_C = 250\text{ A}$, $V_{CC} = 600\text{ V}$ $T_j = 125\text{ °C}$, $V_{CC} = 900\text{ V}$			10 12	mJ mJ			
Mechanical data								
M_{dc}	DC terminals, SI Units	6		8	Nm			
M_{ac}	AC terminals, SI Units	13		15	Nm			
w	SKiiP® 2 System w/o heat sink		3,5		kg			
w	heat sink		8,5		kg			
Thermal characteristics (P16 heat sink; 275 m³/h); " r " reference to temperature sensor								
$R_{th(j-s)I}$	per IGBT			0,09	K/W			
$R_{th(j-s)D}$	per diode			0,25	K/W			
$R_{th(s-a)}$	per module			0,036	K/W			
Z_{th}	R_i (mK/W) (max. values)			$\tau_{i(s)}$				
	1	2	3	4	1	2	3	4
$Z_{th(j-r)I}$	10	69	11	0	1	0,13	0,001	1
$Z_{th(j-r)D}$	28	193	30	0	1	0,13	0,001	1
$Z_{th(r-a)}$	1,7	24	7,6	2,6	494	165	20	0,03



This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee, expressed or implied is made regarding delivery, performance or suitability.



SKiiP 342GDL120-4DU



SKiiP[®] 2

Absolute Maximum Ratings		$T_a = 25\text{ °C}$ unless otherwise specified	
Symbol	Conditions	Values	Units
V_{S1}	stabilized 15 V power supply	18	V
V_{S2}	unstabilized 24 V power supply	30	V
V_{iH}	input signal voltage (high)	15 + 0,3	V
dv/dt	secondary to primary side	75	kV/ μ s
V_{isolIO}	input / output (AC, r.m.s., 2s)	3000	Vac
V_{isol12}	output 1 / output 2 (AC, r.m.s., 2s)	1500	Vac
f_{sw}	switching frequency	5	kHz
f_{out}	output frequency for $I=I_C$; sin.	1	kHz
T_{op} (T_{stg})	operating / storage temperature	- 25 ... + 85	°C

7-pack - integrated intelligent Power System

7-pack
integrated gate driver - brake chopper
SKiiP 342GDL120-4DU


Gate driver features

- CMOS compatible inputs
- Wide range power supply
- Integrated circuitry to sense phase current, heat sink temperature and DC-bus voltage (option)
- Short circuit protection
- Over current protection
- Over voltage protection (option)
- Power supply protected against under voltage
- Interlock of top/bottom switch
- Isolation by transformer
- IEC 60068-1 (climate) 25/85/56

Characteristics		$(T_a = 25\text{ °C})$			
Symbol	Conditions	min.	typ.	max.	Units
V_{S1}	supply voltage stabilized	14,4	15	15,6	V
V_{S2}	supply voltage non stabilized	20	24	30	V
I_{S1}	$V_{S1} = 15\text{ V}$	$67 + 10 \cdot f / f_{max} + 0 \cdot (I_{AC} / A)$			mA
I_{S2}	$V_{S2} = 24\text{ V}$	$67 + 10 \cdot f / f_{max} + 0 \cdot (I_{AC} / A)$			mA
V_{iT+}	input threshold voltage (High)	12,3			V
V_{iT-}	input threshold voltage (Low)	4,6			V
R_{IN}	input resistance	10			k Ω
$t_{d(on)IO}$	input-output turn-on propagation time	20,2			μ s
$t_{d(off)IO}$	input-output turn-off propagation time	25,6			μ s
$t_{pERRRESET}$	error memory reset time	300000			μ s
t_{TD}	top / bottom switch : interlock time				μ s
$I_{analogOUT}$	8 V corresponds to max. current of 15 V supply voltage (available when supplied with 24 V)				A
$I_{Vs1outmax}$	output current at pin				mA
I_{A0max}	output current at pin				mA
V_{OI}	logic low output voltage	0,6			V
V_{OH}	logic high output voltage	30			V
I_{TRIPSC}	over current trip level ($I_{analog OUT} = 10\text{ V}$)				A
I_{TRIPLG}	ground fault protection				A
T_{tp}	over temperature protection	110	120		°C
U_{DCTRIP}	trip level of U_{DC} -protection ($U_{analog OUT} = 9\text{ V}$); (option)				V

For electrical and thermal design support please use SEMISEL.
Access to SEMISEL is via SEMIKRON website <http://www.semikron.com>.

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee, expressed or implied is made regarding delivery, performance or suitability.



Case S 5