




## DUAL SUPPLY OCTAL ECL-TO-TTL

ClockWorks™  
SY100HA643

### FEATURES

- ECL/TTL version of popular ECLinPS™ E111
- 400ps within device skew
- 800ps part-to-part skew
- Latch
- Differential internal design
- VBB output
- Dual supply
- Reset/Enable
- Multiple TTL and ECL power/ground pins
- Fully compatible with Motorola MC100H643
- Higher performance than H643 versions
- Industrial temperature availability
- Available in 28-pin PLCC package

### BLOCK DIAGRAM




### DESCRIPTION

The SY100HA643 is an enhanced dual supply, low skew translating 1:8 clock driver. Devices in the Micrel-Synergy H600 translators series utilize the 28-lead PLCC for optimal power pinning, signal flow through and electrical performance. The dual-supply HA643 is similar to the H641, which is a single-supply 1:9 version of the same function, with higher performance than the H643 versions.

The device features a 48mA TTL output stage, with AC performance specified into a 20pF load capacitance. A Latch is provided on-chip. When LEN is LOW (or left open, in which case it is pulled LOW by the internal pulldowns) the latch is transparent. A HIGH on the enable pin ( $\bar{EN}$ ) forces all outputs LOW.

The 100HA643 is compatible with 100K ECL logic levels.

### PIN CONFIGURATION



### PIN NAMES

Pin	Function
OGND	TTL Output Ground (0V)
OVTTL	Output Vcc (+5.0V)
IGND	Internal TTL GND (0V)
IVT	Internal TTL Vcc (+5.0V)
VEE	ECL VEE (-5.2/-4.5V)
VCCE	ECL Ground (0V)
D, $\bar{D}$	Signal Input (ECL)
VBB	VBB Reference Output
Q0 - Q7	Signal Outputs (TTL)
$\bar{EN}$	Enable Input (ECL)
LEN	Latch Enable Input (ECL)



**TRUTH TABLE**

D	LEN	$\overline{\text{EN}}$	Q
L	L	L	L
H	L	L	H
X	X	H	L

**DC CHARACTERISTICS**

IVT = OVT = 5.0V ±5%; VEE = -4.2V to -5.5V; VCC = GND

Symbol	Parameter	TA = -40°C		TA = 0°C		TA = +25°C		TA = +85°C		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.		
IEE	Power Supply	—	58	—	58	—	58	—	58	mA	VEE Pins Total all OVT and IVT pins
ICCL		—	83	—	83	—	83	—	83	mA	
ICCH		—	73	—	73	—	73	—	73	mA	
VOH	TTL Output HIGH Voltage	2.5 2.0	— —	2.5 2.0	— —	2.5 2.0	— —	2.5 2.0	— —	V	IOH = -3.0mA IOH = -15mA
VOL	TTL Output LOW Voltage	—	0.5	—	0.5	—	0.5	—	0.5	V	IOL = 48mA
Ios	TTL Output Short Circuit Current	-80	-200	-80	-200	-80	-200	-80	-200	mA	VOUT = 0V
IiH	ECL Input HIGH Current	—	225	—	225	—	175	—	175	μA	
IiL	ECL Input LOW Current	0.5	—	0.5	—	0.5	—	0.5	—	μA	
VIH	ECL Input HIGH Voltage	—	—	-1165	-880	-1165	-880	-1165	-880	mV	
VIL	ECL Input LOW Voltage	—	—	-1810	-1475	-1810	-1475	-1810	-1475	mV	
VBB	ECL Output Reference Voltage	-1380	-1260	-1380	-1260	-1380	-1260	-1380	-1260	mV	

**AC CHARACTERISTICS**

IVT = OVT = 5.0V ±5%; VEE = -4.2V to -5.5V ; VCC = GND

Symbol	Parameter	TA = -40°C		TA = 0°C		TA = +25°C		TA = +85°C		Unit	Condition
		Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.		
t <sub>IH</sub>	Propagation Delay to Output D LEN EN	2.3	3.1	2.3	3.1	2.3	3.1	2.3	3.1	ns	CL = 20pF
t <sub>skew</sub>	Within-Device Skew <sup>(1)</sup>	—	0.4	—	0.4	—	0.4	—	0.4	ns	
t <sub>PW</sub>	Pulse Width Out <sup>(2)</sup> HIGH or LOW @ FOUT = 100MHz	4.5	5.5	4.5	5.5	4.5	5.5	4.5	5.5	ns	CL = 20pF
t <sub>S</sub>	Setup Time D	0.75	—	0.75	—	0.75	—	0.75	—	ns	
t <sub>H</sub>	Hold Time D	0.75	—	0.75	—	0.75	—	0.75	—	ns	
t <sub>RR</sub>	Recovery Time LEN EN	1.25 1.25	— —	1.25 1.25	— —	1.25 1.25	— —	1.25 1.25	— —	ns ns	
t <sub>PW</sub>	Minimum Pulse Width LEN EN	1.5 1.5	— —	1.5 1.5	— —	1.5 1.5	— —	1.5 1.5	— —	ns ns	
t <sub>r</sub> t <sub>f</sub>	Rise / Fall times 0.8V — 2.0V	—	1.5	—	1.5	—	1.5	—	1.5	ns	CL = 20pF
f <sub>MAX</sub>	Max. Input Frequency <sup>(3,4)</sup>	160	—	160	—	160	—	160	—	MHz	CL = 20pF

**NOTES:**


1. Within-Device skew defined as identical transitions on similar paths through a device.
2. Pulse width is defined relative to 1.5V measurement points on the output waveform.
3. Frequency at which output levels will meet a 0.8V to 2.0V minimum swing.
4. The f<sub>MAX</sub> value is specified as the minimum guaranteed maximum frequency. Actual operational maximum frequency may be greater.

**PRODUCT ORDERING CODE**

Ordering Code	Package Type	Operating Range
SY100HA643JC	J28-1	Commercial
SY100HA643JCTR	J28-1	Commercial

Ordering Code	Package Type	Operating Range
SY100HA643JI	J28-1	Industrial
SY100HA643JITR	J28-1	Industrial

**28 LEAD PLCC (J28-1)**



- NOTES:
1. DIMENSIONS ARE IN INCHES[MM].
  2. CONTROLLING DIMENSION: INCHES.
  3. DIMENSION DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS, EITHER OF WHICH SHALL NOT EXCEED 0.008[0.203].
  4. LEAD DIMENSION DOES NOT INCLUDE DAMBAR PROTRUSION.
  5. MAXIMUM AND MINIMUM SPECIFICATIONS ARE INDICATED AS FOLLOWS: MAX/MIN
  6. PACKAGE TOP DIMENSION MAY BE SLIGHTLY SMALLER THAN BOTTOM DIMENSION.

Rev. 03