

International Rectifier

Bulletin PD -2.601 rev. A 11/00

HFA08TA60C

HEXFRED™


Ultrafast, Soft Recovery Diode

Features

- Ultrafast Recovery
- Ultrasoft Recovery
- Very Low I_{RRM}
- Very Low Q_{rr}
- Specified at Operating Conditions

Benefits

- Reduced RFI and EMI
- Reduced Power Loss in Diode and Switching Transistor
- Higher Frequency Operation
- Reduced Snubbing
- Reduced Parts Count



$$V_R = 600V$$

$$V_F = 1.8V$$

$$Q_{rr}^* = 40nC$$

$$di_{(rec)}/dt^* = 280A/\mu s$$

* 125°C



TO-220AB

Description

International Rectifier's HFA08TA60C is a state of the art center tap ultra fast recovery diode. Employing the latest in epitaxial construction and advanced processing techniques it features a superb combination of characteristics which result in performance which is unsurpassed by any rectifier previously available. With basic ratings of 600 volts and 4 amps per Leg continuous current, the HFA08TA60C is especially well suited for use as the companion diode for IGBTs and MOSFETs. In addition to ultra fast recovery time, the HEXFRED product line features extremely low values of peak recovery current (I_{RRM}) and does not exhibit any tendency to "snap-off" during the t_b portion of recovery. The HEXFRED features combine to offer designers a rectifier with lower noise and significantly lower switching losses in both the diode and the switching transistor. These HEXFRED advantages can help to significantly reduce snubbing, component count and heatsink sizes. The HEXFRED HFA08TA60C is ideally suited for applications in power supplies and power conversion systems (such as inverters), motor drives, and many other similar applications where high speed, high efficiency is needed.

Absolute Maximum Ratings

	Parameter	Max	Units
V_R	Cathode-to-Anode Voltage	600	V
$I_F @ T_C = 100^\circ C$	Continuous Forward Current	4.0	A
I_{FSM}	Single Pulse Forward Current	25	
I_{FRM}	Maximum Repetitive Forward Current	16	
$P_D @ T_C = 25^\circ C$	Maximum Power Dissipation	25	W
$P_D @ T_C = 100^\circ C$	Maximum Power Dissipation	10	
T_J	Operating Junction and	- 55 to +150	C
T_{STG}	Storage Temperature Range		

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min	Typ	Max	Units	Test Conditions
V _{BR}	Cathode Anode Breakdown Voltage	600			V	I _R = 100μA
V _{FM}	Max Forward Voltage		1.5	1.8	V	I _F = 4.0A
			1.8	2.2		I _F = 8.0A See Fig. 1
			1.4	1.7		I _F = 4.0A, T _J = 125°C
I _{RM}	Max Reverse Leakage Current		0.17	3.0	μA	V _R = V _R Rated See Fig. 2
			44	300		T _J = 125°C, V _R = 0.8 x V _R Rated
C _T	Junction Capacitance		4.0	8.0	pF	V _R = 200V See Fig. 3
L _S	Series Inductance		8.0		nH	Measured lead to lead 5mm from package body

Dynamic Recovery Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min	Typ	Max	Units	Test Conditions
t _{rr}	Reverse Recovery Time		17			I _F = 1.0A, di _F /dt = 200A/μs, V _R = 30V
t _{rr1}	See Fig. 5, 6 & 16		28	42	ns	T _J = 25°C
t _{rr2}			38	57		T _J = 125°C
I _{RRM1}	Peak Recovery Current		2.9	5.2	A	T _J = 25°C
I _{RRM2}	See Fig. 7 & 8		3.7	6.7		T _J = 125°C
Q _{rr1}	Reverse Recovery Charge		40	60	nC	T _J = 25°C
Q _{rr2}			70	105		T _J = 125°C
di _{(rec)M} /dt1	Peak Rate of Fall of Recovery Current		280		A/μs	T _J = 25°C
di _{(rec)M} /dt2	During t _b See Fig. 11 & 12		235			T _J = 125°C

Thermal - Mechanical Characteristics

	Parameter	Min	Typ	Max	Units
T _{lead} ①	Lead Temperature			300	°C
R _{thJC}	Thermal Resistance, Junction to Case			5.0	K/W
R _{thJA} ②	Thermal Resistance, Junction to Ambient			80	
R _{thCS} ③	Thermal Resistance, Case to Heat Sink		0.5		
Wt	Weight		2.0		g
			0.07		(oz)
T	Mounting Torque		6.0	12	Kg-cm
			5.0	10	lbf•in

① 0.063 in. from Case (1.6mm) for 10 sec

② Typical Socket Mount

③ Mounting Surface, Flat, Smooth and Greased




Fig. 1 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current,




Fig. 2 - Typical Reverse Current vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage








Fig. 4 - Maximum Thermal Impedance Z_{thjc} Characteristics

Fig. 5 - Typical Reverse Recovery vs. di_f/dt Fig. 6 - Typical Recovery Current vs. di_f/dt Fig. 7 - Typical Stored Charge vs. di_f/dt Fig. 8 - Typical $di_{(rec)}M/dt$ vs. di_f/dt




Fig. 9 - Reverse Recovery Parameter Test Circuit





Fig. 10 - Reverse Recovery Waveform and Definitions

Bulletin PD-2.601 rev. A 11/00

International
IOR Rectifier



Conforms to JEDEC Outline TO-220AB
Dimensions in millimeters and inches

International
IOR Rectifier

WORLD HEADQUARTERS: 333 Kansas St., El Segundo, California 90245 U.S.A. Tel: (310) 322 3333 Fax: (310) 322 3332
EUROPEAN HEADQUARTERS: Hurst Green, Oxted, Surrey RH8 9BB, U.K. Tel: ++ 44 1883 732020. Fax: ++ 44 1883 733408
IR CANADA: 15 Lincoln Court, Brampton, Markham, Ontario L6T3Z2. Tel: (905) 453 2200. Fax: (905) 475 8801
IR GERMANY: Saalburgstrasse 157, 61350 Bad Homburg, Germany. Tel: ++ 49 6172 96590. Fax: ++ 49 6172 965933
IR ITALY: Via Liguria 49, 10071 Borgaro, Torino, Italy. Tel: ++ 39 11 4510111. Fax: ++ 39 11 4510220
IR FAR EAST: K&H Bldg., 2F, 30-4 Nishi-Ikebukuro 3-Chome, Toshima-Ku, Tokyo, Japan 171. Tel: 81 3 3983 0086
IR SOUTHEAST ASIA: 1 Kim Seng Promenade, Great World City West Tower, 13-11, Singapore 237994. Tel: ++ 65 838 4630
IR TAIWAN: 16 Fl. Suite D-207. Sec. 2, Tun Haw South Road, Taipei, 10673, Taiwan. Tel: 886 2 3377 9936

<http://www.irf.com>

Fax-On-Demand: +44 1883 733420

Data and specifications subject to change without notice.