

PANDUIT PART NO. *	BUNDLE DIA.		A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	F in (mm)	MIN. LOOP TENSILE LBS. (N)	CROSS SECTION	TIP STYLE	WEIGHT lbs/100 pcs. (g)
	MIN. in (mm)	MAX. in (mm)										
1LT2S	.188 (4.8)	1.88 (47.8)	.052 (1.3)	.190 (4.8)	.389 (9.9)	.140 (3.6)	.316 (8.0)	8.30 (211)	50 (222)	STANDARD	CURVED	.284 (129)
1LT3S	.188 (4.8)	3.00 (76.2)	.052 (1.3)	.190 (4.8)	.389 (9.9)	.140 (3.6)	.316 (8.0)	11.5 (292)	50 (222)	STANDARD	CURVED	.385 (175)
1LT4S	.188 (4.8)	4.00 (101.6)	.052 (1.3)	.190 (4.8)	.389 (9.9)	.140 (3.6)	.316 (8.0)	14.7 (373)	50 (222)	STANDARD	CURVED	.490 (222)
1LT4LH	.200 (5.1)	4.00 (101.6)	.075 (1.9)	.300 (7.6)	.600 (15.2)	.250 (6.4)	.515 (13.1)	14.8 (376)	120 (534)	LIGHT HEAVY	CURVED	1.132 (514)
1LT6LH	.200 (5.1)	6.00 (152.4)	.075 (1.9)	.300 (7.6)	.600 (15.2)	.250 (6.4)	.515 (13.1)	21.2 (538)	120 (534)	LIGHT HEAVY	CURVED	1.610 (731)

										DIMENSIONS IN PARENTHESES ARE IN METRIC UNITS									
										PANDUIT SS-27217-ILT-04.PRT									
										CORP. TINLEY PARK, ILLINOIS									
										BELT-TY INLINE-TIE CABLE TIES									
										ILT SERIES									
										UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE:					UNLESS OTHERWISE SPECIFIED,				
										(.X) ± ---- (.XXX) ±.020(.51)					ALL DIMENSIONS ARE GIVEN				
										(.XX) ±.02(.5) ANGLES ± ----					IN INCHES, THIRD ANGLE PROJECTION.				
										DRAWN BY CJW		MAT'L:					SCALE NONE		
7	8/10/04	MJVE		.515 WAS .475 ON ILT4/6LH DIM E			27217	7			DATE 6-9-99						DRAWING NO. SS-27217		DWG A
REV	DATE	BY	CHK	DESCRIPTION			ECN	-	R	CUST	SUP		CHK'D JKG		SIZE				