

Isobar Surge Suppressor

Premium surge, spike and line noise protection



Model #: ISOBAR2-6

- ▶ 2 outlets / 6-ft. cord
- ▶ 600 joule rating
- ▶ All metal housing
- ▶ \$25,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

DESCRIPTION

For more than 20 years, America's leading companies have trusted Tripp Lite's Isobar Premium surge and noise suppressors to protect sensitive computer, networking and telecom equipment. With more than 14 million satisfied customers, the Isobar remains the world's #1 selling premium surge suppressor. Loaded with a generous combination of high quality components, near indestructible all-metal case and enhanced noise filtration system, Isobars offer the highest level of protection. Robust surge suppression circuits with sine-wave tracking offer extreme levels of protection against the heaviest surge conditions exceeding IEEE 587 category A & B specifications and reducing 6,000V test surges to harmless levels under 35 volts. Isobar's unique protection system combines large toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors into a complete surge and EMI/RFI noise reduction system. ISOBAR2-6 offers 2 outlets with network-grade surge suppression rated at 600 joules / 48,000 amps. Widely spaced NEMA 5-15 outlets accommodate up to 2 large transformer plugs. Includes 6 foot AC line cord with space-saving angled input plug and keyhole mounting tabs. Lifetime warranty with \$25,000 Ultimate Lifetime connected equipment Insurance (USA & Canada Only).

PLUG / OUTLETS: Input: NEMA 5-15P / Output: 2 NEMA5-15R / 6 ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz (Requires NEMA 5-15R wall receptacle)

SUPPRESSION: AC: 140V RMS Clamping / 600 joules / 48,000 amps

FORMAT: Corded all-metal strip

KEY BUYING POINTS

- Tripp Lite's ISOBAR is the world's #1 selling premium suppressor series with more than 14 million satisfied customers and a safety-tested history of 20+ years
- Robust surge suppression with sine-wave tracking protects against the heaviest of surge conditions, exceeding IEEE category A&B specifications and reducing 6,000V test surges to harmless levels less than 35 volts
- Multi-component suppression circuits combine toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors
- 2 AC outlets accommodate up to 2 large transformer plugs
- Network grade surge suppression rated at 600 joules / 48,000 amps
- Widely spaced outlets accommodate up to 2 large transformer plugs without blocking outlets
- Lighted power switch confirms power on/off status
- 6 foot AC line cord with space-saving angled input plug
- Keyhole mounting tabs allow permanent installation
- 120V AC, 50/60Hz electrical compatibility
- \$25,000 Ultimate Lifetime Insurance (USA & Canada Only)
- Lifetime product warranty
- UL1449 listed - surge suppression (330V let-through), UL1283 listed - EMI protection, UL1363 listed - power tap, cUL approved to Canadian standards

TYPICAL APPLICATIONS

- Ideal for premium protection of personal computers with peripherals, network and CAD / CAM / CAE workstations, internetworking accessories, telecommunications systems, point of sale equipment, audio / video and home theater systems in any home, office or industrial application.

PACKAGE INCLUDES

- ISOBAR2-6 Surge Suppressor
- Set of 4 outlet safety covers
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview: ISOBAR premium surge and noise suppression system prevents equipment damage and performance problems resulting from damaging transient surges and line noise. Active filter network maintains noise-free output with zero reaction / response time. Rugged all-metal, mountable housing fitted with high quality duplex style output receptacles. 2 outlets, 600 joules AC protection level, less than 35V let through voltage.

Voltage compatibility: 120 VAC

Frequency compatibility: 50/60 Hz

OUTPUT

Output volt amp capacity (amps): 12

Output watt capacity (watts): 1440

Outlet quantity / type: 2 NEMA 5-15R output receptacles, high quality duplex style

Transformer accomodation: Supports up to 2 large transformer plug accessories without covering remaining outlets

INPUT

Input connection type: NEMA 5-15P input plug

Input cord length (ft.): 6

Input cord length (m): 1.8

Recommended electrical service: 120V 15A

LEDS ALARMS & SWITCHES

Switches: Two position red illuminated on/off power switch

AC SURGE / NOISE SUPPRESSION

Protection modes: Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression

AC suppression joule rating: 600 joules

Clamping voltage (RMS): 140V

AC suppression response time: NM = 0 ns. CM = <1 ns

AC suppression surge current rating: 48,000 amps (24,000 NM / 24,000 CM)

AC suppression components used: Metal oxide varistors, toroidal balanced chokes, ferrite rod-core inductors and VHF capacitors.

Safe thermal fusing: Prevents unsafe conditions during extreme extended overvoltages and catastrophic occurences

UL1499 let through rating: 330V - UL Verified

IEEE587 Cat. A ringwave let through: Less than 35 volts

EMI / RFI filtering: 40-80 dB

Immunity: Conforms to IEE 587 / ANSI C62.41

PHYSICAL

Unit Dimensions (HWD/in):	2.5 x 5 x 3.5
Unit Dimensions (HWD/cm):	6.4 x 12.7 x 8.9
Material of construction:	Extruded aluminum
Integrated keyhole mounting tabs:	Metal end caps are fitted with keyhole mounting tabs for wallmount installation
Housing color:	Gray
Receptacle color:	Black
AC line cord color:	Gray

CERTIFICATIONS

UL1449 1998 Rev. (AC Suppression):	UL1449
UL1283 (EMI Filter):	UL1283
UL1363 (Power Tap):	UL1363
cUL / CSA (Canada):	cUL
Approvals:	Exceeds IEEE 587 category A&B specifications

WARRANTY

Product warranty:	Lifetime
Connected equipment insurance (USA and Canada Only):	Up to \$25,000

SPECIAL FEATURES

Appearance:	Rugged all-metal corded strip format with high quality duplex receptacles
--------------------	---

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.