



- No protruding head to cause injury since head is inverted
- No protruding tie tip to cause injury since the tip is trapped between the tie and the foam
- Tie will not slip on the foam since the head will indent the foam to remain captive
- Wide tie body .350" (8.9mm) for improved aesthetics
- Cannot over-tension tie causing bulges in the foam
- Install by hand or use *PANDUIT* GTH installation tool
- Flexible and easy to handle
- No need to heat weld the ends closed
- No cutoff scrap pieces to handle or pick up
- Strong: 124 lb. (550N) minimum loop tensile strength
- Locking wedge is protected from unlocking and from ultraviolet light exposure
- Weather Resistant Nylon 6.6 - Available in 13 ultraviolet colors (to match the foam) that will last 2-3 times longer than normal pigmented colors

NOTE: Ties are installed with the teeth on the inside against the foam.

Part Number:	IT9115-CUV5B
Product Family:	IN-LINE Cable Ties for Playground Applications
Product Line:	IN-LINE Cable Ties
RoHS Compliancy Status:	Compliant
Part Description:	IN-LINE Cable Tie, 15.3", Light-Heavy cross section
Product Type:	Cable Ties
Material:	Ultraviolet (UV) Resistant Nylon 6.6

Color: UV Hunter Green

CSA Certified: No

UL Listed (File #E56854): No

UL Recognized (File #E56854): No

Length (In.): 15.3

Length (mm): 389

Width (In.): .350

Width (mm): 8.9

CE Compliant: Yes

Cross Section: Light-Heavy

Head Height (In.): .300

Head Height (mm): 7.6

Head Width (In.): .556

Head Width (mm): 14.1

Locking Style: Locking

Material Flammability Rating: UL94V-2

Max. Bundle Diameter (In.): 4.53

Max. Bundle Diameter (mm): 115

Max. Continuous Use Temperature: 185°F (85°C)

Min. Loop Tensile Strength (Lbs.): 124

Min. Loop Tensile Strength (N): 550

Std. Pkg. UOM: PK

Thickness (In.): .065

Thickness (mm): 1.7

Tool: Hand Installation Recommended

UOM: PC

Std. Pkg. Qty.: 100

Min. Order Qty.: 100