



ADVANCE TECHNICAL INFORMATION


**CoolMOS Power MOSFET**  
**ISOPLUS220™**

**IXKC 13N80C**

$V_{DSS} = 800 \text{ V}$   
 $I_{D25} = 13 \text{ A}$   
 $R_{DS(on)} = 290 \text{ m}\Omega$


**Electrically Isolated Back Surface**

N-Channel Enhancement Mode  
Low  $R_{DS(on)}$ , High Voltage MOSFET



Symbol	Test Conditions	Maximum Ratings	
$V_{DSS}$	$T_J = 25^\circ\text{C to } 150^\circ\text{C}$	800	V
$V_{GS}$	Continuous	$\pm 20$	V
$I_{D25}$	$T_C = 25^\circ\text{C}$ ; Note 1	13	A
$I_{D90}$	$T_C = 90^\circ\text{C}$ , Note 1	9	A
$I_{D(RMS)}$	Package lead current limit	45	A
$E_{AS}$	$I_D = 4\text{A}$ , $T_C = 25^\circ\text{C}$	670	mJ
$E_{AR}$	$I_D = 10\text{A}$	0.5	mJ
$dv/dt$	$V_{DS} < V_{DSS}$ , $I_F \leq 17\text{A}$ , $T_{VJ} = 150^\circ\text{C}$ $d_s/dt = 100\text{ A}/\mu\text{s}$	6	V/ns
$P_D$	$T_C = 25^\circ\text{C}$	125	W
$T_J$		-55 ... +150	$^\circ\text{C}$
$T_{JM}$		150	$^\circ\text{C}$
$T_{stg}$		-55 ... +125	$^\circ\text{C}$
$T_L$	1.6 mm (0.062 in.) from case for 10 s	300	$^\circ\text{C}$
$V_{ISOL}$	RMS leads-to-tab, 50/60 Hz, $t = 1\text{ minute}$	2500	V~
$F_C$	Mounting force	11 ... 65 / 2.4 ... 11	N/lb
<b>Weight</b>		2	g

**ISOPLUS 220™**



Isolated back surface\*

G = Gate, D = Drain,  
S = Source

\* Patent pending

**Features**

- Silicon chip on Direct-Copper-Bond substrate
  - High power dissipation
  - Isolated mounting surface
  - 2500V electrical isolation
- 3<sup>RD</sup> generation CoolMOS power MOSFET
  - High blocking capability
  - Low on resistance
  - Avalanche rated for unclamped inductive switching (UIS)
- Low thermal resistance due to reduced chip thickness
- Low drain to tab capacitance (<30pF)

**Applications**

- Switched Mode Power Supplies (SMPS)
- Uninterruptible Power Supplies (UPS)
- Power Factor Correction (PFC)
- Welding
- Inductive Heating

**Advantages**

- Easy assembly: no screws or isolation foils required
- Space savings
- High power density

Symbol	Test Conditions	Characteristic Values ( $T_J = 25^\circ\text{C}$ , unless otherwise specified)		
		min.	typ.	max.
$R_{DS(on)}$	$V_{GS} = 10\text{V}$ , $I_D = I_{D90}$ , Note 3 $V_{GS} = 10\text{V}$ , $I_D = I_{D90}$ , Note 3 $T_J = 125^\circ\text{C}$		250 550	290 mΩ mΩ
$V_{GS(th)}$	$V_{DS} = V_{GS}$ , $I_D = 1\text{mA}$	2		4 V
$I_{DSS}$	$V_{DS} = V_{DSS}$ , $V_{GS} = 0\text{V}$ $T_J = 25^\circ\text{C}$ $T_J = 125^\circ\text{C}$		125	25 μA μA
$I_{GSS}$	$V_{GS} = \pm 20\text{V}_{DC}$ , $V_{DS} = 0$			$\pm 100$ nA

COOLMOS is a trademark of Infineon Technology.




Symbol	Test Conditions	Characteristic Values		
		(T <sub>J</sub> = 25°C, unless otherwise specified)		
		min.	typ.	max.
Q <sub>g(on)</sub>	V <sub>GS</sub> = 10 V, V <sub>DS</sub> = 640 V, I <sub>D</sub> = 17 A		83	nC
Q <sub>gs</sub>		9	nC	
Q <sub>gd</sub>		42	nC	
t <sub>d(on)</sub>	V <sub>GS</sub> = 10 V, V <sub>DS</sub> = 640V I <sub>D</sub> = 17 A, R <sub>G</sub> = 4.7 Ω		25	ns
t <sub>r</sub>		15	ns	
t <sub>d(off)</sub>		75	ns	
t <sub>f</sub>		10	ns	
R <sub>thJC</sub>				1.0 K/W
R <sub>thCH</sub>		0.30		K/W

**Reverse Conduction**

Symbol	Test Conditions	Characteristic Values		
		(T <sub>J</sub> = 25°C, unless otherwise specified)		
		min.	typ.	max.
V <sub>SD</sub>	I <sub>F</sub> = 6.5 A, V <sub>GS</sub> = 0 V Note 3		1	1.2 V

- Note: 1. MOSFET chip capability  
 2. Intrinsic diode capability  
 3. Pulse test, t ≤ 300 μs, duty cycle d ≤ 2 %

**ISOPLUS220 OUTLINE**


SYM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	.157	.197	4.00	5.00
A2	.098	.118	2.50	3.00
b	.035	.051	0.90	1.30
b2	.049	.065	1.25	1.65
b4	.093	.100	2.35	2.55
c	.028	.039	0.70	1.00
D	.591	.630	15.00	16.00
D1	.472	.512	12.00	13.00
E	.394	.433	10.00	11.00
E1	.295	.335	7.50	8.50
e	.100 BASIC		2.55 BASIC	
L	.512	.571	13.00	14.50
L1	.118	.138	3.00	3.50
L4	.039	.059	1.00	1.50
T*			42.5°	47.5°

- Note: All terminals are solder plated.  
 1 - Gate  
 2 - Drain  
 3 - Source