



APT60M60JFLL


600V 70A 0.060Ω

POWER MOS 7™

FREDFET

Power MOS 7™ is a new generation of low loss, high voltage, N-Channel enhancement mode power MOSFETS. Both conduction and switching losses are addressed with Power MOS 7™ by significantly lowering  $R_{DS(ON)}$  and  $Q_g$ . Power MOS 7™ combines lower conduction and switching losses along with exceptionally fast switching speeds inherent with APT's patented metal gate structure.

- Lower Input Capacitance
- Lower Miller Capacitance
- Lower Gate Charge,  $Q_g$
- Increased Power Dissipation
- Easier To Drive
- Popular SOT-227 Package

**FAST RECOVERY BODY DIODE**


## MAXIMUM RATINGS

All Ratings:  $T_C = 25^\circ\text{C}$  unless otherwise specified.

| Symbol         | Parameter                                                      | APT60M60JFLL | UNIT                |
|----------------|----------------------------------------------------------------|--------------|---------------------|
| $V_{DSS}$      | Drain-Source Voltage                                           | 600          | Volts               |
| $I_D$          | Continuous Drain Current @ $T_C = 25^\circ\text{C}$            | 70           | Amps                |
| $I_{DM}$       | Pulsed Drain Current <sup>①</sup>                              | 280          |                     |
| $V_{GS}$       | Gate-Source Voltage Continuous                                 | $\pm 30$     | Volts               |
| $V_{GSM}$      | Gate-Source Voltage Transient                                  | $\pm 40$     |                     |
| $P_D$          | Total Power Dissipation @ $T_C = 25^\circ\text{C}$             | 690          | Watts               |
|                | Linear Derating Factor                                         | 5.52         | W/ $^\circ\text{C}$ |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range               | -55 to 150   | $^\circ\text{C}$    |
| $T_L$          | Lead Temperature: 0.063" from Case for 10 Sec.                 | 300          |                     |
| $I_{AR}$       | Avalanche Current <sup>①</sup> (Repetitive and Non-Repetitive) | 70           | Amps                |
| $E_{AR}$       | Repetitive Avalanche Energy <sup>①</sup>                       | 50           | mJ                  |
| $E_{AS}$       | Single Pulse Avalanche Energy <sup>④</sup>                     | 3600         |                     |

## STATIC ELECTRICAL CHARACTERISTICS

| Symbol       | Characteristic / Test Conditions                                                                   | MIN | TYP | MAX       | UNIT    |
|--------------|----------------------------------------------------------------------------------------------------|-----|-----|-----------|---------|
| $BV_{DSS}$   | Drain-Source Breakdown Voltage ( $V_{GS} = 0V, I_D = 250\mu A$ )                                   | 600 |     |           | Volts   |
| $I_{D(on)}$  | On State Drain Current <sup>②</sup> ( $V_{DS} > I_{D(on)} \times R_{DS(on)}$ Max, $V_{GS} = 10V$ ) | 70  |     |           | Amps    |
| $R_{DS(on)}$ | Drain-Source On-State Resistance <sup>②</sup> ( $V_{GS} = 10V, 0.5 I_{D[Cont.]}$ )                 |     |     | 0.060     | Ohms    |
| $I_{DSS}$    | Zero Gate Voltage Drain Current ( $V_{DS} = V_{DSS}, V_{GS} = 0V$ )                                |     |     | 250       | $\mu A$ |
|              | Zero Gate Voltage Drain Current ( $V_{DS} = 0.8 V_{DSS}, V_{GS} = 0V, T_C = 125^\circ\text{C}$ )   |     |     | 1000      |         |
| $I_{GSS}$    | Gate-Source Leakage Current ( $V_{GS} = \pm 30V, V_{DS} = 0V$ )                                    |     |     | $\pm 100$ | nA      |
| $V_{GS(th)}$ | Gate Threshold Voltage ( $V_{DS} = V_{GS}, I_D = 5mA$ )                                            | 3   |     | 5         | Volts   |

CAUTION: These Devices are Sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed.

APT Website - <http://www.advancedpower.com>

# DYNAMIC CHARACTERISTICS

APT60M60JFLL

| Symbol       | Characteristic                 | Test Conditions                                                                                                | MIN | TYP   | MAX | UNIT |
|--------------|--------------------------------|----------------------------------------------------------------------------------------------------------------|-----|-------|-----|------|
| $C_{iss}$    | Input Capacitance              | $V_{GS} = 0V$<br>$V_{DS} = 25V$<br>$f = 1 \text{ MHz}$                                                         |     | 12290 |     | pF   |
| $C_{oss}$    | Output Capacitance             |                                                                                                                |     | 2200  |     |      |
| $C_{rss}$    | Reverse Transfer Capacitance   |                                                                                                                |     | 138   |     |      |
| $Q_g$        | Total Gate Charge <sup>③</sup> | $V_{GS} = 10V$<br>$V_{DD} = 0.5 V_{DSS}$<br>$I_D = I_D [\text{Cont.}] @ 25^\circ\text{C}$                      |     | 282   |     | nC   |
| $Q_{gs}$     | Gate-Source Charge             |                                                                                                                |     | 65    |     |      |
| $Q_{gd}$     | Gate-Drain ("Miller") Charge   |                                                                                                                |     | 125   |     |      |
| $t_{d(on)}$  | Turn-on Delay Time             | $V_{GS} = 15V$<br>$V_{DD} = 0.5 V_{DSS}$<br>$I_D = I_D [\text{Cont.}] @ 25^\circ\text{C}$<br>$R_G = 0.6\Omega$ |     | 21    |     | ns   |
| $t_r$        | Rise Time                      |                                                                                                                |     | 16    |     |      |
| $t_{d(off)}$ | Turn-off Delay Time            |                                                                                                                |     | 51    |     |      |
| $t_f$        | Fall Time                      |                                                                                                                |     | 12    |     |      |

# SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS

| Symbol    | Characteristic / Test Conditions                                                   | MIN                       | TYP | MAX | UNIT          |
|-----------|------------------------------------------------------------------------------------|---------------------------|-----|-----|---------------|
| $I_S$     | Continuous Source Current (Body Diode)                                             |                           |     | 70  | Amps          |
| $I_{SM}$  | Pulsed Source Current <sup>①</sup> (Body Diode)                                    |                           |     | 280 |               |
| $V_{SD}$  | Diode Forward Voltage <sup>②</sup> ( $V_{GS} = 0V$ , $I_S = -I_D [\text{Cont.}]$ ) |                           |     | 1.3 | Volts         |
| $dv/dt$   | Peak Diode Recovery $dv/dt$ <sup>⑤</sup>                                           |                           |     | 15  | V/ns          |
| $t_{rr}$  | Reverse Recovery Time<br>( $I_S = -I_D [\text{Cont.}]$ , $di/dt = 100A/\mu s$ )    | $T_j = 25^\circ\text{C}$  |     | 300 | ns            |
|           |                                                                                    | $T_j = 125^\circ\text{C}$ |     | 600 |               |
| $Q_{rr}$  | Reverse Recovery Charge<br>( $I_S = -I_D [\text{Cont.}]$ , $di/dt = 100A/\mu s$ )  | $T_j = 25^\circ\text{C}$  | 1.8 |     | $\mu\text{C}$ |
|           |                                                                                    | $T_j = 125^\circ\text{C}$ | 7.4 |     |               |
| $I_{RRM}$ | Peak Recovery Current<br>( $I_S = -I_D [\text{Cont.}]$ , $di/dt = 100A/\mu s$ )    | $T_j = 25^\circ\text{C}$  | 16  |     | Amps          |
|           |                                                                                    | $T_j = 125^\circ\text{C}$ | 30  |     |               |

# THERMAL CHARACTERISTICS

| Symbol          | Characteristic      | MIN | TYP | MAX  | UNIT               |
|-----------------|---------------------|-----|-----|------|--------------------|
| $R_{\theta JC}$ | Junction to Case    |     |     | 0.18 | $^\circ\text{C/W}$ |
| $R_{\theta JA}$ | Junction to Ambient |     |     | 40   |                    |

① Repetitive Rating: Pulse width limited by maximum junction temperature.

② Pulse Test: Pulse width < 380  $\mu s$ , Duty Cycle < 2%


③ See MIL-STD-750 Method 3471

④ Starting  $T_j = +25^\circ\text{C}$ ,  $L = 1.47\text{mH}$ ,  $R_G = 25\Omega$ , Peak  $I_L = 70\text{A}$

⑤  $dv/dt$  numbers reflect the limitations of the test circuit rather than the device itself.  $I_S \leq -I_D [\text{Cont.}]$   $di/dt \leq 700A/\mu s$   $V_R \leq V_{DSS}$   $T_j \leq 150^\circ\text{C}$

APT Reserves the right to change, without notice, the specifications and information contained herein.

# SOT-227 (ISOTOP®) Package Outline



Dimensions in Millimeters and (Inches)