

P6KE6.8A Series

600 Watt Peak Power Surmetic™ -40 Zener Transient Voltage Suppressors

Unidirectional*

The P6KE6.8A series is designed to protect voltage sensitive components from high voltage, high energy transients. They have excellent clamping capability, high surge capability, low zener impedance and fast response time. These devices are ON Semiconductor's exclusive, cost-effective, highly reliable Surmetic™ axial leaded package and is ideally-suited for use in communication systems, numerical controls, process controls, medical equipment, business machines, power supplies and many other industrial/consumer applications.

Specification Features:

- Working Peak Reverse Voltage Range – 5.8 to 171 V
- Peak Power – 600 Watts @ 1 ms
- ESD Rating of Class 3 (>16 KV) per Human Body Model
- Maximum Clamp Voltage @ Peak Pulse Current
- Low Leakage < 5 μ A above 10 V
- Maximum Temperature Coefficient Specified
- UL 497B for Isolated Loop Circuit Protection
- Response Time is typically < 1 ns

Mechanical Characteristics:

CASE: Void-free, Transfer-molded, Thermosetting plastic

FINISH: All external surfaces are corrosion resistant and leads are readily solderable

MAXIMUM LEAD TEMPERATURE FOR SOLDERING:

230°C, 1/16" from the case for 10 seconds

POLARITY: Cathode indicated by polarity band

MOUNTING POSITION: Any

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Peak Power Dissipation (Note 1.) @ $T_L \leq 25^\circ\text{C}$	P_{PK}	600	Watts
Steady State Power Dissipation @ $T_L \leq 75^\circ\text{C}$, Lead Length = 3/8" Derated above $T_L = 75^\circ\text{C}$	P_D	5.0 50	Watts mW/°C
Thermal Resistance, Junction-to-Lead	$R_{\theta JL}$	20	°C/W
Forward Surge Current (Note 2.) @ $T_A = 25^\circ\text{C}$	I_{FSM}	100	Amps
Operating and Storage Temperature Range	T_J, T_{stg}	- 55 to +175	°C


1. Nonrepetitive current pulse per Figure 4 and derated above $T_A = 25^\circ\text{C}$ per Figure 2.
2. 1/2 sine wave (or equivalent square wave), PW = 8.3 ms, duty cycle = 4 pulses per minute maximum.

*Please see P6KE6.8CA – P6KE200CA for Bidirectional devices.




ON Semiconductor™

<http://onsemi.com>



AXIAL LEAD
CASE 17
STYLE 1



L = Assembly Location
P6KExxxA = ON Device Code
YY = Year
WW = Work Week


ORDERING INFORMATION

Device	Package	Shipping
P6KExxxA	Axial Lead	1000 Units/Box
P6KExxxARL	Axial Lead	4000/Tape & Reel

P6KE6.8A Series

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 3.5\text{ V Max. @ } I_F \text{ (Note 6.)} = 50\text{ A}$)

Symbol	Parameter
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
V_{RWM}	Working Peak Reverse Voltage
I_R	Maximum Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
ΘV_{BR}	Maximum Temperature Coefficient of V_{BR}
I_F	Forward Current
V_F	Forward Voltage @ I_F



P6KE6.8A Series

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted, $V_F = 3.5\text{ V Max. @ } I_F$ (Note 6.) = 50 A)

Device	Device Marking	V_{RWM} (Note 3.)	I_R @ V_{RWM}	Breakdown Voltage			V_C @ I_{PP} (Note 5.)		θV_{BR}
				V_{BR} (Note 4.) (Volts)			@ I_T	I_{PP}	
		Volts	μA	Min	Nom	Max	mA	Volts	%/ $^\circ\text{C}$
P6KE6.8A	P6KE6.8A	5.8	1000	6.45	6.80	7.14	10	10.5	0.057
P6KE7.5A	P6KE7.5A	6.4	500	7.13	7.51	7.88	10	11.3	0.061
P6KE8.2A	P6KE8.2A	7.02	200	7.79	8.2	8.61	10	12.1	0.065
P6KE9.1A	P6KE9.1A	7.78	50	8.65	9.1	9.55	1	13.4	0.068
P6KE10A	P6KE10A	8.55	10	9.5	10	10.5	1	14.5	0.073
P6KE11A	P6KE11A	9.4	5	10.5	11.05	11.6	1	15.6	0.075
P6KE12A	P6KE12A	10.2	5	11.4	12	12.6	1	16.7	0.078
P6KE13A	P6KE13A	11.1	5	12.4	13.05	13.7	1	18.2	0.081
P6KE15A	P6KE15A	12.8	5	14.3	15.05	15.8	1	21.2	0.084
P6KE16A	P6KE16A	13.6	5	15.2	16	16.8	1	22.5	0.086
P6KE18A	P6KE18A	15.3	5	17.1	18	18.9	1	25.2	0.088
P6KE20A	P6KE20A	17.1	5	19	20	21	1	27.7	0.09
P6KE22A	P6KE22A	18.8	5	20.9	22	23.1	1	30.6	0.092
P6KE24A	P6KE24A	20.5	5	22.8	24	25.2	1	33.2	0.094
P6KE27A	P6KE27A	23.1	5	25.7	27.05	28.4	1	37.5	0.096
P6KE30A	P6KE30A	25.6	5	28.5	30	31.5	1	41.4	0.097
P6KE33A	P6KE33A	28.2	5	31.4	33.05	34.7	1	45.7	0.098
P6KE36A	P6KE36A	30.8	5	34.2	36	37.8	1	49.9	0.099
P6KE39A	P6KE39A	33.3	5	37.1	39.05	41	1	53.9	0.1
P6KE43A	P6KE43A	36.8	5	40.9	43.05	45.2	1	59.3	0.101
P6KE47A	P6KE47A	40.2	5	44.7	47.05	49.4	1	64.8	0.101
P6KE51A	P6KE51A	43.6	5	48.5	51.05	53.6	1	70.1	0.102
P6KE56A	P6KE56A	47.8	5	53.2	56	58.8	1	77	0.103
P6KE62A	P6KE62A	53	5	58.9	62	65.1	1	85	0.104
P6KE68A	P6KE68A	58.1	5	64.6	68	71.4	1	92	0.104
P6KE75A	P6KE75A	64.1	5	71.3	75.05	78.8	1	103	0.105
P6KE82A	P6KE82A	70.1	5	77.9	82	86.1	1	113	0.105
P6KE91A	P6KE91A	77.8	5	86.5	91	95.5	1	125	0.106
P6KE100A	P6KE100A	85.5	5	95	100	105	1	137	0.106
P6KE110A	P6KE110A	94	5	105	110.5	116	1	152	0.107
P6KE120A	P6KE120A	102	5	114	120	126	1	165	0.107
P6KE130A	P6KE130A	111	5	124	130.5	137	1	179	0.107
P6KE150A	P6KE150A	128	5	143	150.5	158	1	207	0.108
P6KE160A	P6KE160A	136	5	152	160	168	1	219	0.108
P6KE170A	P6KE170A	145	5	162	170.5	179	1	234	0.108
P6KE180A	P6KE180A	154	5	171	180	189	1	246	0.108
P6KE200A	P6KE200A	171	5	190	200	210	1	274	0.108

3. A transient suppressor is normally selected according to the maximum working peak reverse voltage (V_{RWM}), which should be equal to or greater than the dc or continuous peak operating voltage level.
4. V_{BR} measured at pulse test current I_T at an ambient temperature of 25°C
5. Surge current waveform per Figure 4 and derate per Figures 1 and 2.
6. 1/2 sine wave (or equivalent square wave), PW = 8.3 ms, duty cycle = 4 pulses per minute maximum.

P6KE6.8A Series




Figure 1. Pulse Rating Curve




Figure 2. Pulse Derating Curve




Figure 3. Capacitance versus Breakdown Voltage




Figure 4. Pulse Waveform




Figure 5. Steady State Power Derating




Figure 6. Typical Derating Factor for Duty Cycle

P6KE6.8A Series

APPLICATION NOTES

RESPONSE TIME

In most applications, the transient suppressor device is placed in parallel with the equipment or component to be protected. In this situation, there is a time delay associated with the capacitance of the device and an overshoot condition associated with the inductance of the device and the inductance of the connection method. The capacitance effect is of minor importance in the parallel protection scheme because it only produces a time delay in the transition from the operating voltage to the clamp voltage as shown in Figure 7.

The inductive effects in the device are due to actual turn-on time (time required for the device to go from zero current to full current) and lead inductance. This inductive effect produces an overshoot in the voltage across the equipment or component being protected as shown in Figure 8. Minimizing this overshoot is very important in the application, since the main purpose for adding a transient suppressor is to clamp voltage spikes. The P6KE6.8A series has very good response time, typically < 1 ns and negligible inductance. However, external inductive effects could produce unacceptable overshoot. Proper circuit layout,

minimum lead lengths and placing the suppressor device as close as possible to the equipment or components to be protected will minimize this overshoot.

Some input impedance represented by Z_{in} is essential to prevent overstress of the protection device. This impedance should be as high as possible, without restricting the circuit operation.

DUTY CYCLE DERATING

The data of Figure 1 applies for non-repetitive conditions and at a lead temperature of 25°C . If the duty cycle increases, the peak power must be reduced as indicated by the curves of Figure 6. Average power must be derated as the lead or ambient temperature rises above 25°C . The average power derating curve normally given on data sheets may be normalized and used for this purpose.

At first glance the derating curves of Figure 6 appear to be in error as the 10 ms pulse has a higher derating factor than the 10 μs pulse. However, when the derating factor for a given pulse of Figure 6 is multiplied by the peak power value of Figure 1 for the same pulse, the results follow the expected trend.

TYPICAL PROTECTION CIRCUIT





Figure 7.




Figure 8.

P6KE6.8A Series

UL RECOGNITION*

The entire series including the bidirectional CA suffix has *Underwriters Laboratory Recognition* for the classification of protectors (QVGV2) under the UL standard for safety 497B and File #E 116110. Many competitors only have one or two devices recognized or have recognition in a non-protective category. Some competitors have no recognition at all. With the UL497B recognition, our parts successfully passed several tests including Strike Voltage

Breakdown test, Endurance Conditioning, Temperature test, Dielectric Voltage-Withstand test, Discharge test and several more.

Whereas, some competitors have only passed a flammability test for the package material, we have been recognized for much more to be included in their protector category.

*Applies to P6KE6.8A, CA – P6KE200A, CA.


P6KE6.8A Series

OUTLINE DIMENSIONS

Transient Voltage Suppressors – Axial Leaded

600 Watt Peak Power Surmetic™ –40

SURMETIC 40
CASE17-02
ISSUE C



NOTES:

1. CONTROLLED DIMENSION: INCH
2. LEAD FINISH AND DIAMETER UNCONTROLLED IN DIM F.
3. CATHODE BAND INDICATES POLARITY

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.330	0.350	8.38	8.89
B	0.130	0.145	3.30	3.68
D	0.037	0.043	0.94	1.09
K	---	0.050	---	1.27
F	1.000	1.250	25.40	31.75

STYLE 1:

- PIN 1. ANODE
2. CATHODE

P6KE6.8A Series

SURMETIC is a trademark of Semiconductor Components Industries, LLC.

ON Semiconductor is a trademark and  is a registered trademark of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

Literature Fulfillment:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

JAPAN: ON Semiconductor, Japan Customer Focus Center
4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031
Phone: 81-3-5740-2700
Email: r14525@onsemi.com

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local Sales Representative.