

Unit: mm

5.0 ± 0.2

7.4 ± 0.2

2.0 Max. NOT SOLDERED

2.3

1.0

3.3 ± 0.3

26.5 ± 0.1

2 - 0.7 Max

2 - 0.5 Max

2.54

1.5

1 2

0.45 ± 0.1

1: Anode
2: Cathode

■ Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

★ I_{EP} の条件は, duty 10%, Pulse width 1 msec. The condition of I_{EP} is duty 10%, Pulse width 1 msec

Conventional Part No.	Lighting Color	Lens Color	I _O		I _F	V _F		λ _P	Δλ	I _F	I _R	
			Typ	Min		Typ	Max	Typ	Typ		Max	V _R
LN273RPX	Red	Red Diffused	0.4	0.15	15	2.2	2.8	700	100	20	5	4
LN373GPX	Green	Green Diffused	2.0	0.75	20	2.2	2.8	565	30	20	10	4
LN473YPX	Amber	Amber Diffused	1.5	0.60	20	2.2	2.8	590	30	20	10	4
LN873RPX	Orange	Red Diffused	1.5	0.60	20	2.1	2.8	630	40	20	10	3
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	μA	V

