

# Line Conditioner

Automatic voltage regulation with surge protection



## Model #: LS1006M

- ▶ Automatically adjusts low or high voltage
- ▶ 1000 watts continuous
- ▶ 6 NEMA 5-15R outlets
- ▶ \$25,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

## DESCRIPTION

Tripp Lite's LS1006M automatic voltage regulation system offers complete protection from brownouts, overvoltages and transient surges for computers, printers, fax machines and more. Transformer-based voltage correction circuits maintain usable 120V nominal AC output during brownouts as low as 93V and overvoltages to 141V. Network grade equipment protection offers AC surge and noise suppression rated at 720 joules. Single telephone line surge suppression protects modem, fax machine, cordless phones and other devices with a dialup/DSL line connection. Supports loads up to 1000 watts. Includes 6 NEMA5-15R outlets, 6-ft. line cord and 3 diagnostic LEDs that display boost, trim and normal regulation operation. Two year warranty.

## KEY BUYING POINTS

- Maintains usable 120V nominal output during brownouts as low as 93V and overvoltages as high as 141V
- 1000 watts output power rating supports 120V loads up to 8.3 amps
- Network grade surge suppression rated at 720 joules
- EMI/RFI noise filtering
- 3 diagnostic LEDs indicate boost, trim and normal LC operation
- 6 protected NEMA5-15R outlets
- 6-ft. AC power cord with standard NEMA5-15P input plug
- Single line surge suppression protects modem, fax machine and other system peripherals with a phone line connection from damage due to surges on phone / DSL lines
- 2 year manufacturers product warranty

## TYPICAL APPLICATIONS

- Maintains usable output voltage during severe brownouts and overvoltages for printers, fax machines, computers, audio/video equipment, CAD/CAM/CAE workstations, network nodes, file servers, phone systems, point-of-sale terminals, and other applications requiring steady input power.

## PACKAGE INCLUDES

- LS1006M Line Conditioner
- Warranty information
- Instruction manual

## COMPLETE SPECIFICATIONS

### OUTPUT

Output watt capacity (watts): 1000

<b>Output volt amp capacity (VA):</b>	1000
<b>Output nominal voltage:</b>	120v / 60Hz
<b>Outlet quantity / type:</b>	6 NEMA5-15R

**INPUT**

<b>Input cord length (ft.):</b>	6.00
<b>Input cord length (m):</b>	1.83
<b>Maximum input amps / watts:</b>	1250 watts / 8.3 amps

**LEDS ALARMS & SWITCHES**

<b>Front panel LEDs:</b>	3 LEDs indicate voltage boost, trim and normal operation
--------------------------	--

**PHYSICAL**

<b>Unit Dimensions (HWD/in):</b>	5.5 x 4.75 x 4.75
<b>Unit Dimensions (HWD/cm):</b>	13.5 x 12 x 11.5
<b>Form factors supported:</b>	Small Tower
<b>Material of construction:</b>	Poly-resin
<b>Shipping weight (lbs):</b>	7.00
<b>Shipping weight (kg):</b>	3.18

**CERTIFICATIONS**

<b>Certifications:</b>	UL1012 (USA), cUL (Canada), NOM (Mexico), FCC Part 68 (telephone communications)
------------------------	--

**WARRANTY**

<b>Product warranty:</b>	2 years
<b>Connected equipment insurance (USA and Canada Only):</b>	Up to \$25,000

**SPECIAL FEATURES**

<b>Additional Information:</b>	Single line telephone / DSL line surge suppression jacks
--------------------------------	--

*The policy of Tripp Lite is one of continuous improvement.  
Specifications are subject to change without notice.  
Therefore, your product may vary slightly from what is currently listed.*



**Tripp Lite World Headquarters**  
1111 W. 35th Street  
Chicago, IL 60609 USA

**Customer Support**  
(773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.