

LX9506

Input Cable Assembly

PRODUCTION DATA SHEET

DESCRIPTION


cable assembly that is used to connect AWG#26 wire. This cable assembly is Linfinity's standard line of backlight designed to save users the job of obtaining inverter products. The connector housing housing, pin, wire, and crimp-tools in is interconnectable and compatible with addition to the assembly of an evaluation PC boards mounted with the Molex* board. 53261 series 5-pin SMT header. The housing and pins are crimp-terminated to

The LX9506 is an input-connector 18-inch (457mm) lengths of UL1061

KEY FEATURES

- Used for Interconnection of **Backlight Inverter Connector** (Molex 53261) to Power, Ground, and Control Signal
- Generous 18-inch (457mm) Lead Length to accommodate Most **Applications**
- Pre-Stripped Ends Facilitate Ease of Hook-up
- Leads Color-Coded for Quick and Accurate Termination
- Wire is 300 Volt Rated to 80°C, PVC Insulated and is Stranded in a 7X #34 Configuration

IMPORTANT: For the most current data, consult MICROSEMI's website: http://www.microsemi.com



Item	Description
1	Molex* 51021 Series
2	Molex* 50079 Series
3	UL 1061, 26 AWG, Red Wire
4	UL 1061, 26 AWG, Blue Wire
5	UL 1061, 26 AWG, Black Wire
6	UL 1061, 26 AWG, Orange Wire
7	UL 1061, 26 AWG, Green Wire

Pin #	Color Coding
1	Red
2	Blue
3	Black
4	Orange
5	Green

* Molex is a Registered Trademark of Molex, Inc.

MODEL ORDER INFO

LX9506

