PANDUIT

MBH-TLR



- For applications that require various bundle diameters
 - Supplied in reels of 82.50 feet (25.0m), 200.00 feet (60.9m), 250.00 feet (76.2m) or 1000.00 feet (304.8m)
 - Provides job site versatility with minimum inventory
 - Packaging speeds removal of steel and includes bundle diameter cut-off guide
 - Available in AISI 304 stainless steel for general-purpose applications
 - Available in AISI 316 stainless steel for the most corrosive environments
- Note: For the recommended installation tools, select from the list of part number in the table below

■ Part Number	MBH-TLR
■ RoHS Compliancy Status	Compliant
■ Part Description	Custom length continuous ba
■ Material	Stainless Steel Type 304
■ Color	natural
■ Length (ft.)	250
■ Length (m)	76
■ Width (In.)	.31
■ Width (mm)	7.9
■ Banding Head	MTHH-C
Cross Section	Heavy
■ Max. Bundle Diameter (In.)	Any
■ Max. Bundle Diameter (mm)	Any
■ Min. Bundle Diameter (In.)	.50
 Min. Bundle Diameter (mm) 	12.7
• Min. Loop Tensile Strength (Lbs.	250
■ Min. Loop Tensile Strength (N)	1112
■ Pricing Description	Custom Banding, 304 Steel,
■ Thickness (In.)	.010
■ Thickness (mm)	.25
■ Tool	GS4MT, HTMT, PPTMT, ST
■ Used with Buckle	MTHH-C
■ Min. Order UOM	RL
■ Min. Order Qty.	1
■ BOM Qty. (# of Pkgs.)	

