


MOTOROLA SC (XSTRS/R F)

6367254 MOTOROLA SC (XSTRS/R F)


96D 82435 D
T-29-27

Rating	Symbol	MD2218,A,F	MD2218AF	Unit	
		MD2219,A,F	MD2219AF		
Collector-Emitter Voltage	V _{CEO}	30	40	Vdc	
Collector-Base Voltage	V _{CBO}	60	75	Vdc	
Emitter-Base Voltage	V _{EBO}	5.0	6.0	Vdc	
Collector Current — Continuous	I _C	500		mAdc	
		One Die	All Die Equal Power		
Total Device Dissipation @ T _A = 25°C	P _D			mW	
		MD2218,A, MD2219,A	575	625	mW/°C
		MD2218F,AF, MD2219F,AF	350	400	
		MQ2218,A, MQ2219,A	400	600	
Derate above 25°C					
		MD2218,A, MD2219,A	3.29	3.57	
		MD2218F,AF, MD2219F,AF	2.0	2.28	
		MQ2218,A, MQ2219,A	2.28	3.42	
Total Device Dissipation @ T _C = 25°C	P _D			Watts	
		MD2218,A, MD2219,A	1.8	2.5	mW/°C
		MD2218F,AF, MD2219F,AF	1.0	2.0	
		MQ2218,A, MQ2219,A	0.9	3.6	
Derate above 25°C					
		MD2218,A, MD2219,A	10.3	14.3	
		MD2218F,AF, MD2219F,AF	5.71	11.4	
		MQ2218,A, MQ2219,A	5.13	20.5	
Operating and Storage Junction Temperature Range	T _J , T _{stg}	- 65 to + 200		°C	


MD2218,A,F,AF
MD2219,A,AF
MQ2218,A
MQ2219,A



MD2218,A
MD2219,A
CASE 654-07, STYLE 1



MD2218F,AF
MD2219F,AF
CASE 610A-04, STYLE 1



MQ2218,A
MQ2219,A
CASE 607-04, STYLE 1

DUAL
AMPLIFIER TRANSISTOR
NPN SILICON

THERMAL CHARACTERISTICS

Characteristic	Symbol	One Die	All Die Equal Power	Unit
Thermal Resistance, Junction to Case	R _{θJC}	MD2218,A, MD2219,A	97	70
		MD2218F,AF, MD2219F,AF	175	87.5
		MQ2218,A, MQ2219,A	195	48.8
Thermal Resistance, Junction to Ambient	R _{θJA} (1)	MD2218,A, MD2219,A	304	280
		MD2218F,AF, MD2219F,AF	500	438
		MQ2218,A, MQ2219,A	438	292
Coupling Factors			Junction to Ambient	Junction to Case
		MD2218,A, MD2219,A	84	44
		MD2218F,AF, MD2219F,AF	75	0
		MQ2218,A, MQ2219,A (Q1-Q2)	57	0
		(Q1-Q3 or Q1-Q4)	55	0

(1) R_{θJA} is measured with the device soldered into a typical printed circuit board.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS					
Collector-Emitter Breakdown Voltage(2) (I _C = 10 mAdc, I _B = 0)	V _{(BR)CEO}				Vdc
		MD2218,A,F, MD2219,A, MQ2218,A, MQ2219,A	30	—	—
		MD2218AF, MD2219AF	40	—	—
Collector-Base Breakdown Voltage (I _C = 10 μAdc, I _E = 0)	V _{(BR)CBO}				Vdc
		MD2218,A,F, MD2219,A, MQ2218,A, MD2219,A	60	—	—
		MD2218AF, MD2219AF	75	—	—

MOTOROLA SMALL-SIGNAL SEMICONDUCTORS



6367254 MOTOROLA SC (XSTRS/R F)
 MD2218,A,F,AF, MD2219,A,AF, MQ2218,A, MQ2219,A

96D 82436 D

T-29-27

ELECTRICAL CHARACTERISTICS (continued) (T_A = 25°C unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
Emitter-Base Breakdown Voltage (I _E = 10 μAdc, I _C = 0)	V _{(BR)EBO}	5.0 6.0	— —	— —	Vdc
Collector Cutoff Current (V _{CE} = 50 Vdc, V _{EB(off)} = 3.0 Vdc)	I _{CEV}	20 15	— —	— —	nAdc
Base Cutoff Current (V _{CE} = 50 Vdc, V _{EB(off)} = 3.0 Vdc)	I _{BL}	30	—	—	nAdc

ON CHARACTERISTICS(2)

Characteristic	Symbol	Min	Typ	Max	Unit
DC Current Gain (I _C = 0.1 mAdc, V _{CE} = 10 Vdc)	h _{FE}	20 35	50 45	— —	—
(I _C = 1.0 mAdc, V _{CE} = 10 Vdc)		25 50	55 55	— —	
(I _C = 10 mAdc, V _{CE} = 10 Vdc)		35 75	65 85	— —	
(I _C = 150 mAdc, V _{CE} = 1.0 Vdc)		20 50	65 65	— —	
(I _C = 150 mAdc, V _{CE} = 10 Vdc)		40 100	30 120	120 300	
(I _C = 300 mAdc, V _{CE} = 10 Vdc)		25 30	75 75	— —	
Collector-Emitter Saturation Voltage (I _C = 150 mAdc, I _B = 15 mAdc)	V _{CE(sat)}	— —	0.2 —	0.4 0.3	Vdc
(I _C = 300 mAdc, I _B = 30 mAdc)		— —	0.35 —	1.2 0.9	
Base-Emitter Saturation Voltage (I _C = 150 mAdc, I _B = 15 mAdc)	V _{BE(sat)}	0.6 0.6	0.95 1.0	1.3 1.2	Vdc
(I _C = 300 mAdc, I _B = 30 mAdc)		— —	— —	2.0 1.8	

SMALL-SIGNAL CHARACTERISTICS

Characteristic	Symbol	200	250	—	Unit
Current-Gain — Bandwidth Product (I _C = 20 mAdc, V _{CE} = 20 Vdc, f = 100 MHz)	f _T	200	250	—	MHz
Output Capacitance (V _{CB} = 10 Vdc, I _E = 0, f = 100 kHz)	C _{obo}	—	3.5	8.0	pF
Input Capacitance (V _{EB} = 0.5 Vdc, I _C = 0, f = 100 kHz)	C _{ibo}	— —	15 18	20 25	pF

5

6367254 MOTOROLA SC (XSTRS/R F)
 MD2218,A,F,AF, MD2219,A,AF, MQ2218,A, MQ2219,A

96D 82437 D

T-29-27

ELECTRICAL CHARACTERISTICS (continued) ($T_A = 25^\circ\text{C}$ unless otherwise noted.)

Characteristic	Symbol	Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS					
Delay Time	$(V_{CC} = 30\text{ Vdc}, I_C = 150\text{ mAdc}, V_{BE(off)} = 0.5\text{ Vdc}, I_{B1} = 15\text{ mAdc})$ MD2218,F, MD2219 MD2218A,AF, MD2219A,AF	—	—	20	μs
Rise Time		—	—	40	μs
Storage Time	$(V_{CC} = 30\text{ Vdc}, I_C = 150\text{ mAdc}, I_{B1} = I_{B2} = 15\text{ mAdc})$ MD2218,F, MD2219 MD2218A,AF, MD2219A,AF	—	—	280	μs
Fall Time		—	—	70	μs
				60	μs

(2) Pulse Test: Pulse Width $\leq 300\ \mu\text{s}$, Duty Cycle $\leq 2.0\%$.



FIGURE 1 - NORMALIZED DC CURRENT GAIN




FIGURE 2 - "ON" VOLTAGES





FIGURE 3 - TEMPERATURE COEFFICIENTS



6367254 MOTOROLA SC (XSTRS/R F)



96D 82438 D

MD2218,A,F,AF, MD2219,A,AF, MQ2218,A, MQ2219,A



T-29-27

NOISE FIGURE



($V_{CE} = 10 \text{ Vdc}$, $T_A = 25^\circ\text{C}$)



5



SWITCHING TIME CHARACTERISTICS



6367254 MOTOROLA SC (XSTRS/R F)
 MD2218,A,F,AF, MD2219,A,AF, MQ2218,A, MQ2219,A

96D 82439 D

T-29-27

FIGURE 10 - TURN-OFF BEHAVIOR




FIGURE 11 - DELAY AND RISE TIME EQUIVALENT TEST CIRCUIT





FIGURE 12 - STORAGE TIME AND FALL TIME EQUIVALENT TEST CIRCUIT

