

MICRO

ELECTRONICS

查询MI51T供应信息


捷多邦, 专业PCB打样工厂, 24小时加急出货

MI51T

INFRARED
EMITTING
DIODE

DESCRIPTION

MI51T is GaAlAs infrared emitting diode molded in T-1 3/4 standard 5mm diameter clear transparent lens.



ABSOLUTE MAXIMUM RATINGS

Forward Current (Continuous)	100mA
Pulse Forward Current	1A*
Reverse Voltage (Continuous)	5V
Power Dissipation	75mW
Operating Temperature Range	-25 to +85°C
Lead Soldering Temperature (1/16" from body)	260°C for 5 sec.

* Pulse Width = 10μs, Duty Ratio = 0.01.

ELECTRO-OPTICAL CHARACTERISTICS

(Ta=25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	CONDITIONS
Radiant Power Output	Po	1.0			mW	IF=20mA
Forward Voltage	VF		1.2	1.6	V	IF=20mA
Reverse Current	IR			100	μA	VR=5V
Half Intensity Beam Angle	θHI		50		degree	IF=20mA
Peak Wavelength	λp		940		nm	IF=20mA
Spectrum Line Half Width	Δλ		45		nm	IF=20mA

MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong, Fax No. 2341 0321 Telex: 43510 Micro Hx. Tel: 2343 0181-5



MISIT

