


5 Amp Schottky Rectifier MS506



Dim.	Inches		Millimeter		Notes
	Minimum	Maximum	Minimum	Maximum	
A	.188	.260	4.78	6.50	Dia.
B	1.00	---	25.4	---	
C	.285	.375	7.24	9.52	
D	.046	.056	1.17	1.42	Dia.

PLASTIC D0201AD

Microsemi
Catalog Number

MS506

Working
Peak Reverse
Voltage

60V

Repetitive
Peak Reverse
Voltage

60V

- Schottky Barrier Rectifier
- Guard Ring Protection
- 175°C Junction Temperature
- High Current Capability

Electrical Characteristics

Average forward current
Average forward current
Maximum surge current
Max peak forward voltage
Max peak forward voltage
Max peak reverse current
Typical junction capacitance

$I_F(AV)$ 5.0 Amps
 $I_F(AV)$ 5.0 Amps
 I_{FSM} 300 Amps
 V_{FM} .52 Volts
 V_{FM} .65 Volts
 I_{RM} 250 μ A
 C_J 355 pF

$T_A = 139^\circ\text{C}$, Square wave, $R_{\theta JL} = 11^\circ\text{C/W}$, $L = 1/8"$
 $T_A = 127^\circ\text{C}$, Square wave, $R_{\theta JL} = 14.7^\circ\text{C/W}$, $L = 3/8"$
8.3ms, half sine, $T_J = 175^\circ\text{C}$
 $I_{FM} = 1.0\text{A}$; $T_J = 25^\circ\text{C}^*$
 $I_{FM} = 5.0\text{A}$; $T_J = 25^\circ\text{C}^*$
 V_{RRM} , $T_J = 25^\circ\text{C}$
 $V_R = 5.0\text{V}$, $T_J = 25^\circ\text{C}$

*Pulse test: Pulse width 300 μ sec, Duty cycle 2%

Thermal and Mechanical Characteristics

Storage temperature range
Operating junction temp range
Maximum thermal resistance


T_{STG}
 T_J
 $L = 3/8"$ $R_{\theta JL}$
 $L = 1/8"$ $R_{\theta JL}$

-55°C to 175°C
 -55°C to 175°C
 14.7°C/W
 11°C/W

Junction to Lead
Junction to Lead

Weight

.032 ounces (1.0 grams) typical



COLORADO

800 Hoyt Street
Broomfield, CO. 80020
PH: (303) 469-2161
FAX: (303) 466-3775

4-6-00 Rev. 1

MS506

Figure 1
Typical Forward Characteristics




Figure 3
Typical Junction Capacitance




Figure 2
Typical Reverse Characteristics

