

Omni Smart UPS System

Line-interactive UPS corrects severe brownouts and overvoltages



Cisco
Compatible

Cisco Systems | Technology
Developed for
the future

Model #: OMNISMART500

- ▶ 500VA line interactive, tower UPS system
- ▶ Corrects brownouts and overvoltages from 75 to 147V
- ▶ 6 protected outlets (3 UPS supported / 3 surge-only)
- ▶ USB port with HID protocol support, cabling and PowerAlert UPS Monitoring Software included
- ▶ Single line tel/DSL line surge suppression
- ▶ \$200,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

DESCRIPTION

Tripp Lite's OMNI SMART 500 line interactive UPS system offers voltage regulation, surge suppression and long lasting battery support for personal computers, internetworking equipment and other sensitive electronics. Supports entry level PC systems for up to 30 minutes during power failures so that connected equipment can be shutdown without data loss. Automatic Voltage Regulation (AVR) circuits regulate brownouts as low as 75 volts and overvoltages as high as 147 back to normal 120V levels without consuming battery power. Offers complete desktop power protection in an attractive black upright tower configuration. Includes 3 battery supported outlets for computer, monitor and one vital system peripheral, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support. USB port enables optional unattended system shutdown without data loss in the case of extended power failure, USB cabling and PowerAlert software included. HID-compliant USB port also enables direct integration with built-in power management and auto-shutdown features of Windows and MAC OS X. Built-in dataline protection jacks offer protection of a single dialup phone/DSL line. Built-in audible alarm and 4 front panel LEDs indicate line power status, battery power status, battery low/replace status and overload status. 500VA / 300 watt power handling ability supports entry-level PCs, network workstations, point-of-sale equipment, small business phone systems, audio/video equipment and home theater systems. Offers 5 minutes battery runtime with a full load of 500VA/300 watts and 17 minutes with a half load of 250VA/150 watts. Supports battery replacement via built-in access panel. 2 year warranty. \$200,000 connected equipment insurance (USA & Canada only).

KEY BUYING POINTS

- OMNI SMART 500 line interactive UPS system offers voltage regulation and battery support, plus complete AC and dialup/DSL line surge suppression
- Supports entry level PC systems for up to 30 minutes during power failures to enable a safe system shutdown
- Supports a maximum load of 500VA/300 watts for 5 minutes and a half load of 250VA/150 watts for 17 minutes
- Automatic Voltage Regulation (AVR) circuits correct brownouts as low as 75 volts and overvoltages as high as 147 back to normal 120 volt levels without using battery power
- Attractive black tower configuration
- Includes 3 battery supported outlets, plus 3 additional surge suppression-only outlets, 6 foot AC line cord (all NEMA 5-15)
- Built-in USB port supports PowerAlert UPS Power Management Software that's included along with cabling to provide safe, unattended system shutdown during blackouts. Provides monitoring of site power conditions, full UPS status and fault warnings.
- HID-compliant USB port enables integration with built-in power management and auto-shutdown features of Windows and Mac OS X.
- Supports Tripp Lite's WatchDog Service Monitoring/Rebooting Software (part# WATCHDOGSW)
- Built-in dataline suppression jacks protect a single dialup phone / DSL line
- Built-in audible alarm and 4 front panel LEDs indicate UPS system and line power status
- 500VA / 300 watt power handling ability supports a variety of computer, internetworking, telecom and consumer electronics equipment
- Supports battery replacement via built-in access panel
- Compatible with 120V / 60Hz applications for USA, Canada, Mexico and more
- 2 year manufacturer's warranty
- \$200,000 connected equipment insurance (USA & Canada only)

TYPICAL APPLICATIONS

- Entry-level PCs, networked workstations, point-of-sale equipment, small business phone systems, audio/video equipment and home theater systems. Ideal for sensitive electronic applications in areas where brownouts and overvoltages are common.

OPTIONS & ACCESSORIES

- USB Hubs-accessories: [U202-004-R](#), [U205-004-R](#), [U022-010](#)
- Circuit Tester: [CT120](#)
- Watchdog software: [WATCHDOGSW](#)
- Wallmount Bracket: [UPSWM](#)
- Extended warranties: 3 Year [WEXT3-OMNI](#), 5 Year [WEXT5-OMNI](#)

PACKAGE INCLUDES

- OMNI SMART 500 UPS System
- PowerAlert software and cabling
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview: Line interactive tower UPS system protects PCs, network workstations and other sensitive electronics from blackouts, brownouts, overvoltages and line noise. Maintains AC output during blackouts and continuously corrects brownouts and overvoltages from 75 to 147 volts back to normal 120V levels. Includes HID compliant USB monitoring port with cabling, TEL / DSL surge suppression, surge only outlets and LED indicators. PowerAlert software included.

Voltage compatibility: 120VAC

Frequency compatibility: 60Hz

OUTPUT

Output volt amp capacity (VA): 500

Output watt capacity (watts): 300

Output nominal voltage: 120VAC

Output voltage regulation: LINE MODE: Sine wave line voltage 120V (-18% / +8%), BATTERY MODE: PWM sine wave output 120V +/-5%

Output frequency regulation: LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz

Outlet quantity / type: 6 NEMA 5-15R

INPUT

Maximum input amps: 10A / 1200 watts

Input connection type: NEMA 5-15P (space saving right-angle plug)

Input cord length: 6 ft., 16 gauge

Recommended electrical service: 15A 120V

BATTERY

Full load runtime: 5 minutes (500VA)

Half load runtime: 17 minutes (250VA)

DC system voltage: 12 VDC

Typical battery lifespan: 3-6 years, depending on usage

Battery recharge rate: 2-4 hours to 90%

Replacement Battery Cartridge: RBC51

VOLTAGE REGULATION

Voltage regulation description: Automatic Voltage Regulation (AVR) circuits maintain clean, regulated computer-grade 120V nominal output, without using battery power, during brownouts to 75V and overvoltages to 147V

Overvoltage correction: Input voltages between 128 and 147V AC are reduced by 12%

Direct pass through: Input voltages between 108 and 127V AC are passed on to connected equipment unchanged

Brownout correction: Input voltages between 93 and 107V AC are boosted by 14%

Severe brownout correction: Input voltages between 75 and 92V AC are boosted by 30%

LEDS ALARMS & SWITCHES

Front panel LEDs: 4 front panel LEDs indicate line power status, battery power status, battery low/replace status and overload

Alarms: Audible alarm with 15 second delay sounds to indicate loss of utility power. Alarm can be silenced by pressing front panel alarm cancel button. Once silenced, alarm will re-sound when approximately 2 minutes runtime remain.

Switches: Includes 2 front panel switches — one main on/off power switch and one dual function "alarm cancel" / "self test" button

SURGE / NOISE SUPPRESSION

AC surge suppression: 480 joules

AC suppression response time: Instantaneous

Dataline suppression: Tel/DSL

EMI / RFI AC noise suppression: Yes

PHYSICAL

Shipping weight (lbs): 15.4

Shipping weight (kg): 7.0

Unit weight (lbs): 14

Unit weight (kg): 6.4

Unit Dimensions (HWD/in): 8.5 x 5 x 6.5

Unit Dimensions (HWD/cm): 21.6 x 12.7 x 16.5

Shipping Dimensions (HWD/in): 12 x 8.25 x 9.25

Shipping Dimensions (HWD/cm): 30.5 x 21 x 23.5

Material of construction: PVC

Form factors supported: Tower

Cooling method: Convection

Battery Access: Battery access door allows user replacement of UPS batteries.

ENVIRONMENTAL

Operating Temperature: +32 to +104 degrees Fahrenheit
0 to +40 degrees Celsius

Storage Temperature: +5 to +122 degrees Fahrenheit
-15 to +50 degrees Celsius

Relative Humidity: 0 to 95%, non-condensing

COMMUNICATIONS

Network monitoring port: HID compliant USB monitoring port

Software and cabling included:	USB cabling and PowerAlert software included.
WatchDog compatibility:	Yes, compatible with Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment - ideal for unattended kiosk applications

LINE / BATTERY TRANSFER

Transfer time from line power to battery mode:	2-4 milliseconds
Low voltage transfer to battery power:	Switches to battery power as line voltage decreases to 75 volts or less. Resets back to line power mode as line voltage increases to 79V or higher.
High voltage transfer to battery power:	Switches to battery power as line voltage increases to 147 volts or higher. Resets back to line power mode as line voltage decreases to 143V or less.

CERTIFICATIONS

Certifications:	Tested to UL1778 (USA), Tested to CSA (Canada), Class B (emissions), NOM (Mexico), FCC Part 68 / Industry Canada (telecommunications)
------------------------	---

WARRANTY

Optional coverage:	3-5 year warranties, plus next day and on-site warranty coverage available. Contact Tripp Lite for additional information.
Product warranty:	2 year product warranty
Connected equipment insurance (USA and Canada Only):	\$200,000 connected equipment insurance (USA and Canada only)

SPECIAL FEATURES

Cold Start:	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance:	Attractive black tower UPS

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.