

Omni Smart UPS System

Line-interactive, tower battery backup with hospital grade plug and receptacles



Cisco
Compatible

Cisco Systems Technology
Solutions for
the future

Model #: OMNISMART700HG

- ▶ 700VA line interactive tower UPS system
- ▶ Hospital grade plug and 4 NEMA5-15R hospital grade output receptacles
- ▶ Corrects brownouts and overvoltages from 75 to 147V without using battery power
- ▶ Enhanced DB9 communications port
- ▶ MSRP: \$462.00

DESCRIPTION

Tripp Lite's OMNI SMART 700HG offers UPS protection, built-in line interactive voltage regulation, intelligent monitoring and unattended shutdown capability. 700VA power handling capacity supports computers, internetworking equipment and other critical loads during commercial power failures. Line interactive voltage regulation corrects brownouts as low as 75V and overvoltages as high as 147V back to normal 120V levels, saving battery reserves for use only during complete power failures. Includes 4 hospital grade outlets, diagnostic LEDs and built-in DB9 communications port that works with web downloadable PowerAlert Software and cabling to provide automatic unattended shutdown of connected network and PC applications.

KEY BUYING POINTS

- Ideal UPS protection for mission critical equipment and computers where hospital-grade input / output connections are required
- Provides connected equipment with continuous power during short and long duration loss of commercial power
- Line-interactive voltage regulation corrects brownouts and overvoltages from 75 to 147 volts back to usable 120v output levels, without using battery power
- Hospital-grade plug and outlets offer added degree of safety to input/output connections
- Supports loads up to 700VA / 425 watts
- 22 minutes half load runtime (with 350VA load), 9 minutes full load runtime (with 700VA load)
- Hospital grade input plug and 4 NEMA5-15R hospital grade output receptacles
- 1-DB9 serial port for network interface; SNMP compatible
- Surge protection and EMI/RFI noise filtering
- PowerAlert UPS monitoring and auto-shutdown software available for free download from www.tripplite.com
- Includes complete cabling for remote monitoring via PowerAlert software
- 4 diagnostic LEDs indicate AC present, on battery, voltage correction & battery low/replace
- Battery replacement door
- 2 year product warranty

TYPICAL APPLICATIONS

- Ideal UPS protection for network workstations, small office file servers and PC systems

PACKAGE INCLUDES

- OMNI SMART 700HG UPS System
- RS-232 monitoring cable
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:	Line Interactive UPS system with hospital grade plug and outlets, automatic voltage regulation, AC surge suppression and RS-232 remote monitoring port
Voltage compatibility:	120 V AC
Frequency compatibility:	60 Hz

OUTPUT

Output volt amp capacity (VA):	700
Output watt capacity (watts):	425
Output nominal voltage:	120V nominal
Output voltage regulation:	LINE MODE: Sine wave line voltage 120V (-18% / +8%) BATTERY MODE: PWM sine wave output 120V +/-5%
Output frequency regulation:	LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz
Outlet quantity / type:	4 NEMA5-15R Hospital Grade Output Receptacles

INPUT

Maximum input amps:	3.8A / 460 watts
Input connection type:	NEMA 5-15P Hospital-Grade
Input cord length:	6 ft, 14 gauge
Recommended electrical service:	15A 120V

BATTERY

Full load runtime:	9 minutes (700VA)
Half load runtime:	22 minutes (350VA)
DC system voltage:	12 VDC
Typical battery lifespan:	3-6 years, depending on usage
Battery recharge rate:	2-4 hours to 90%

VOLTAGE REGULATION

Voltage regulation description:	Automatic Voltage Regulation (AVR) circuits maintain clean, regulated computer-grade 120V nominal output, without using battery power, during brownouts to 75V and overvoltages to 147V
Overvoltage correction:	Input voltages between 128 and 147V AC are reduced by 12%
Direct pass through:	Input voltages between 108 and 127V AC are passed on to connected equipment unchanged
Brownout correction:	Input voltages between 93 and 107V AC are boosted by 14%
Severe brownout correction:	Input voltages between 75 and 92V AC are boosted by 30%

LEDS ALARMS & SWITCHES

Front panel LEDs:	4 front-panel indicator LEDs to display line power status, battery power status, battery low/replace status and voltage regulation operation
Alarms:	Audible alarm indicates power failure conditions, silenceable via alarm cancel switch. Once cancelled, alarm will resume when approximately 2 minutes of battery operation remain (assuming full load).
Switches:	Yes, includes 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions

SURGE / NOISE SUPPRESSION

AC suppression response time:	Instantaneous
EMI / RFI AC noise suppression:	Yes
PHYSICAL	
Shipping weight (lbs):	22
Shipping weight (kg):	10.0
Unit weight (lbs):	20
Unit weight (kg):	9.1
Unit Dimensions (HWD/in):	10.75 x 5.25 x 7.25
Unit Dimensions (HWD/cm):	27.3 x 13.3 x 18.4
Material of construction:	PVC
Form factors supported:	Tower, wall mountable with optional UPSWM accessory
Cooling method:	Convection
Battery Access:	Battery access door allows hot swap battery replacement without powering connected equipment off
ENVIRONMENTAL	
Operating Temperature:	+32 to +104 degrees Fahrenheit 0 to +40 degrees Celsius
Storage Temperature:	+5 to +122 degrees Fahrenheit -15 to +50 degrees Celsius
Relative Humidity:	0 to 95%, non-condensing
COMMUNICATIONS	
Network monitoring port:	Includes built-in basic DB9 monitoring port
Software and cabling included:	PowerAlert UPS monitoring software available for free download from www.tripplite.com , includes complete RS-232 cabling
SNMP compatibility:	External accessory "SNMP-SOLO" SNMP / Web adapter available
LINE / BATTERY TRANSFER	
Transfer time from line power to battery mode:	2-4 milliseconds
Low voltage transfer to battery power:	75V (resets to line power as voltage increases to 79V)
High voltage transfer to battery power:	147V (resets to line power as voltage decreases to 143V)
CERTIFICATIONS	
Certifications:	UL1778 (USA, Series AGOM700KSR61), cUL (Canada), FCC Class A (emissions)
WARRANTY	
Optional coverage:	3 year, 5 year, next day and on-site warranty coverage available
Product warranty:	2 year product warranty
SPECIAL FEATURES	
Cold Start:	Yes, inverter can be "cold started" to enable temporary AC output during a power failure
Appearance:	Attractive gray tower UPS

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.